



REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHERWOOD INDUSTRIAL PARK

PHASE 3 BLDGS 5 & 6 SW CENTURY DRIVE, SHERWOOD, OR



SHEET INDEX	
C0.00	CIVIL COVER SHEET
C0.01	GENERAL CIVIL NOTES AND LEGEND
C1.00	EXISTING CONDITIONS PLAN
	TOPOGRAPHIC SURVEY 1 OF 3
C1.10	OVERALL SITE PLAN
C1.13	SITE PLAN - BUILDINGS 5 & 6
C1.15	FIRE ACCESS PLAN
C1.16	SITE PHOTOMETRIC PLAN
C1.23	GRADING PLAN - BUILDINGS 5 & 6
C1.24	GRADING ENLARGEMENT
C1.33	STORMWATER PLAN - BUILDINGS 5 & 6
C1.43	WATER AND SANITARY PLAN - BUILDINGS 5 & 6
C1.50	EROSION AND SEDIMENT CONTROL COVER SHEET
C1.51	CLEARING AND DEMOLITION EROSION AND SEDIMENT CONTROL PLAN
C1.52	MASS GRADING, AND STABILIZATION EROSION / SED. CONTROL PLAN
C1.53	UTILITY CONSTRUCTION EROSION / SED. CONTROL PLAN
C1.54	FOUNDATION PLAN EROSION / SED. CONTROL PLAN
C1.55	EROSION AND SEDIMENT CONTROL DETAILS
C5.10	CIVIL DETAILS
C5.11	CIVIL DETAILS
C5.12	CIVIL DETAILS
C5.13	STORMWATER DETAILS
C5.14	CITY OF SHERWOOD STANDARD DETAILS
L0.01	LANDSCAPE AND GENERAL INFORMATION
L0.02	CWS SCHEDULE AND NOTES
L1.10	PLANTING PLAN
L1.11	PLANTING PLAN
L2.10	IRRIGATION PLAN
L2.11	IRRIGATION PLAN
L5.10	PLANTING DETAILS
L5.11	STORMWATER AND IRRIGATION DETAILS
L5.12	DRIP IRRIGATION DETAILS

OWNER/DEVELOPER

ORWA SHERWOOD, LLC
ATTN: BRENDA CHRISTINA
8320 NE HIGHWAY 99E
VANCOUVER, WA 98665
PHONE:
E-MAIL: bchristina@mobinv.net

ARCHITECT

MACKENZIE
ATTN: SCOTT MOORE
1515 SE WATER AVE, SUITE 100
PORTLAND, OR 97214
PH: (503) 224-9560
E-MAIL: smore@mcknze.com

CIVIL ENGINEER

MACKENZIE
ATTN: BOB FRENTRESS JR, P.E.
1515 SE WATER AVE, #100
PORTLAND, OR 97214
PHONE: (503) 224-9560
FAX: (503) 228-1285
E-MAIL: rlf@mcknze.com

LANDSCAPE ARCHITECT

MACKENZIE
ATTN: STEVEN TUTTLE
1515 SE WATER AVE, SUITE 100
PORTLAND, OR 97214
PH: (503) 224-9560
FAX: (503) 228-1285
E-MAIL: stuttle@mcknze.com

PLANNER

MACKENZIE
ATTN: BRIAN VARRICCHIONE
1515 SE WATER AVE, SUITE 100
PORTLAND, OR 97214
PH: (503) 224-9560
FAX: (503) 228-1285
E-MAIL: bvarricchione@mcknze.com

SURVEYOR

NORTHWEST SURVEYING, INC.
ATTN: CLINT STUBBS
1815 NW 169TH PLACE, SUITE 2090
BEAVERTON, OR 97006
PH: (503) 848-2127
E-MAIL: clint@nwsrvy.com

WASHINGTON COUNTY TAX LOT NO.

TAX LOT 25129D000150

SITE ADDRESS

15028 SW CENTURY DRIVE, SHERWOOD, OR 97140

SITE ZONING

LIGHT INDUSTRIAL (LI)

SUBJECT SITE AREA NOTE

PROJECT LOT AREA = 4.07 AC (PHASE 3)

BENCH MARK, DATUM ELEVATION

ELEVATIONS AND CONTOURS ARE BASED ON WASHINGTON COUNTY BENCHMARK NUMBER 103. THE BENCHMARK IS A 3" BRASS DISK SET IN CONCRETE AT THE SOUTHWEST CORNER OF THE INTERSECTION OF SW TUALATIN-SHERWOOD ROAD AND THE R/R CROSSING, AND HAS AN ELEVATION OF 171.38 FEET ON THE NGVD 1929 DATUM.

BASIS OF BEARING

THE BASIS OF BEARINGS FOR THIS SURVEY IS WASHINGTON COUNTY SURVEY NO. 28065

TOWNSHIP, RANGE, AND SECTION

SE 1/4 OF SEC 29 T2S R1W, W.M.

REVISION SCHEDULE		
Delta	Issued As	Issue Date

PUBLIC TRANSPORTATION GENERAL NOTES

- ALL CONSTRUCTION, MATERIALS, AND WORKMANSHIP SHALL CONFORM TO THE LATEST STANDARDS AND PRACTICE OF THE CITY OF SHERWOOD AND THE CURRENT EDITION OF THE "STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION" AS PREPARED BY ODOT AND APWA.
- CURRENT CITY OF SHERWOOD TRANSPORTATION SERVICES STANDARD DETAILS SHALL BE UTILIZED IN THE CONSTRUCTION OF THE TRANSPORTATION ELEMENTS OF THESE PLANS.
- STREET SIGNING AND STRIPING SHALL BE INSTALLED BY THE DEVELOPER. ALL STREET SIGNS AND STRIPING SHALL BE INSTALLED PER THE MUTCD.
- ALL CONSTRUCTION WITHIN PUBLIC RIGHT-OF-WAY SHALL HAVE AN APPROVED TRAFFIC CONTROL PLAN AND RIGHT-OF-WAY PERMIT PRIOR TO ANY ON-SITE CONSTRUCTION ACTIVITY.
- PAVING WILL NOT BE ALLOWED DURING WET OR COLD WEATHER. ALL PAVING SHALL BE IN CONFORMANCE WITH THE GEOTECHNICAL REPORT.
- ANY SIGNIFICANT DEVIATIONS FROM THE PLANS WILL REQUIRE A REQUEST FROM THE APPLICANT'S ENGINEER AND APPROVAL FROM THE CITY'S ENGINEER.
- ALL PAVEMENT SHALL BE STRAIGHT CUT PRIOR TO PAVING. EXISTING PAVEMENT SHALL BE REMOVED AS NECESSARY TO PROVIDE A SMOOTH TRANSITION FOR BOTH RIDE AND DRAINAGE.
- ALL ADA PEDESTRIAN RAMPS SHOWN ON THE PLANS AND ON THE DETAIL SHEETS SHALL BE CONSTRUCTED WITH THE PROJECT. WHERE THE SIDEWALK ENDS AT THE PROPERTY LINE, A PEDESTRIAN RAMP SHALL BE PROVIDED TO ACCOMMODATE WHEEL CHAIR ACCESS.
- SUBGRADE PREPARATION DURING WET OR WINTER TIME CONSTRUCTION IS USUALLY/OFTEN NOT FEASIBLE. A WET OR WINTER TIME PLAN SHALL BE SUBMITTED TO CITY OF SHERWOOD, DEVELOPMENT ENGINEERING STAFF FOR REVIEW AND APPROVAL IF THE CONTRACTOR PLANS TO COMMENCE WITH CONSTRUCTION DURING WET WEATHER CONDITIONS. IF PAVING FROM OCTOBER 15TH TO MARCH 30TH, A WET WEATHER SUBGRADE PREPARATION PLAN IS REQUIRED. THE SUBGRADE MUST BE OVER EXCAVATED AND A GEOTEXTILE LINER USED. THE INSPECTOR SHALL APPROVE A COMPLETE PROOF ROLL TEST ON BOTH SIDES OF THE STREET.
- ALL TRAFFIC SIGNALS SHALL REMAIN IN OPERATION DURING CONSTRUCTION ACTIVITIES, EXCEPT AS INDICATED ON THE PLANS. ANY DAMAGE CAUSED BY THE CONTRACTOR OR ANY OF ITS AFFILIATES TO THE EXISTING TRAFFIC SIGNAL CONDUIT, WIRING, POLES, MAST ARMS, SIGNAL INDICATORS, LOOP DETECTORS, AND OTHER RELATED COMPONENTS SHALL BE REPORTED WITHIN 24 HOURS UNLESS OTHERWISE APPROVED BY ENGINEER. IF THIS REPAIR CAN NOT BE COMPLETED IN ALLOTTED TIME, WORK WILL BE DONE BY THE CITY OR ITS DESIGNEE AND ALL COSTS INCLUDING ANY OVERHEAD COSTS SHALL BE INVOICED TO THE CONTRACTOR.
- CONTRACTOR SHALL REPORT ALL DAMAGE IMMEDIATELY TO THE CITY'S ENGINEERING DEPARTMENT.

DEMOLITION NOTES

- INSTALL EROSION CONTROL MEASURES AND TEMPORARY FENCING PRIOR TO ANY DEMOLITION ACTIVITIES.
- DEMOLISH AND REMOVE ALL STRUCTURES AND ASSOCIATED FEATURES (APPURTENANCES), AS SHOWN.
- DEMOLISH ALL PAVED AREAS ON SITE AS SHOWN, DOWN TO NATIVE SUBGRADE.
- ALL VEGETATION AND DELETERIOUS MATERIALS WITHIN THE LIMITS OF WORK SHALL BE STRIPPED AND REMOVED FROM THE SITE PRIOR TO GRADING WORK, UNLESS NOTED OTHERWISE (I.E. PROTECTED TREES).
- PROTECT ALL EXISTING LANDSCAPING AT AND BEYOND LIMITS OF WORK.
- PROTECT ALL UNDERGROUND UTILITY SERVICES AND CONDUIT UNLESS NOTED OTHERWISE.
- WHERE APPLICABLE, VERIFY DISCONNECT OF GAS AND ELECTRIC WITH UTILITY. CUT/CAP UTILITY SERVICES (STORMWATER AND SANITARY WITHIN 5 FEET OF EDGE OF R.O.W.) CAP WATERLINE ON OWNER'S SIDE OF METER AND PERFORM OTHER DEMOLITION TASKS AS REQUIRED. ADDITIONAL REMOVALS MAY BE REQUIRED BY THE AUTHORITIES HAVING JURISDICTION AND THE CONTRACTOR SHALL CONFIRM ACCORDINGLY PRIOR TO BID.

GENERAL NOTES

- ALL WORK SHALL CONFORM TO THE CURRENT STANDARD SPECIFICATIONS AND REQUIREMENTS OF THE LOCAL JURISDICTION AND THE CURRENT AMERICAN PUBLIC WORKS ASSOCIATION STANDARDS FOR PUBLIC WORKS CONSTRUCTION.
- THE SURVEY INFORMATION SHOWN AS A BACKGROUND SCREEN IS BASED ON A SURVEY BY OTHERS AND IS SHOWN FOR REFERENCE ONLY. CONTRACTOR TO VERIFY ALL EXISTING CONDITIONS WITH HIS OWN RESOURCES PRIOR TO START OF ANY CONSTRUCTION.
- CONTRACTOR MUST COMPLY WITH LOCAL AND STATE REQUIREMENTS TO NOTIFY ALL UTILITY COMPANIES FOR LINE LOCATIONS SEVENTY-TWO (72) HOURS (MINIMUM) PRIOR TO START OF WORK. DAMAGE TO UTILITIES SHALL BE CORRECTED AT THE CONTRACTOR'S EXPENSE.
- CONTRACTOR SHALL ADJUST ALL STRUCTURES IMPACTED BY CONSTRUCTION IMPROVEMENTS TO NEW FINISH GRADES.
- REQUEST BY THE CONTRACTOR FOR CHANGES TO THE PLANS MUST BE APPROVED BY THE ENGINEER.
- ALL WORK WITHIN THE PUBLIC RIGHT-OF-WAY REQUIRES A PUBLIC WORKS PERMIT.
- CONTRACTOR SHALL PROVIDE THE ENGINEER OF RECORD WITH AS-BUILT PLANS AT LEAST 2 WEEKS PRIOR TO REQUIRING AGENCY SIGN OFF ON PERMITS FOR OCCUPANCY.

CONSTRUCTION NOTES

- ALL CURB RADII ARE 3' UNLESS OTHERWISE NOTED ON PLANS.
- CONTRACTOR SHALL PREPARE AND PROVIDE SUBMITTAL FOR APPROVAL BY ARCHITECTURAL AND ENGINEERING TEAM MEETING CODE MINIMUM LIGHTING LEVELS AND INCLUDING POLE FOUNDATION DESIGN. REFER TO PERFORMANCE SPECIFICATIONS FOR SITE ELECTRICAL FOR MORE INFORMATION.
- CONTRACTOR MAY ATTEMPT TO REMOVE EXISTING CURB & GUTTER WITHOUT DAMAGING EDGE OF ASPHALT. IF ASPHALT EDGE IS NOT DAMAGED AND MEETS THE APPROVAL OF THE CITY INSPECTOR, CONTRACTOR MAY POUR NEW CURB & GUTTER AGAINST EXISTING ASPHALT EDGE. IF ASPHALT EDGE IS DAMAGED, CONTRACTOR SHALL SAWCUT ASPHALT 3' FROM FACE OF CURB AND REPAVE.

GRADING NOTES

- ~~ROUGH GRADING~~: ROUGH GRADE TO ALLOW FOR DEPTH OF BUILDING SLABS, PAVEMENTS, BASE COURSES, AND TOPSOIL PER DETAILS AND SPECIFICATIONS.
- ~~FINISH GRADING~~: BRING ALL FINISH GRADES TO APPROXIMATE LEVELS INDICATED. WHERE GRADES ARE NOT OTHERWISE INDICATED, HARDSCAPE FINISH GRADES ARE TO BE THE SAME AS ADJACENT SIDEWALKS, CURBS, OR THE OBVIOUS GRADE OF ADJACENT STRUCTURE. SOFTSCAPE GRADES (INCLUDING ADDITIONAL DEPTH OF TOPSOIL) SHALL BE SET 6 INCHES BELOW BUILDING FINISHED FLOORS WHERE ABUTTING BUILDINGS, 1-2 INCHES WHERE ABUTTING WALKWAYS OR CURBS, OR MATCHING OTHER SOFTSCAPE GRADES. GRADE TO UNIFORM LEVELS OR SLOPES BETWEEN POINTS WHERE GRADES ARE GIVEN. ROUND OFF SURFACES, AVOID ABRUPT CHANGES IN LEVELS. AT COMPLETION OF JOB AND AFTER BACKFILLING BY OTHER CRAFTS HAS BEEN COMPLETED, REFILL AND COMPACT AREAS WHICH HAVE SETTLED OR ERODED TO BRING TO FINAL GRADES.
- ~~EXCAVATION~~: EXCAVATE FOR SLABS, PAVING, AND OTHER IMPROVEMENTS TO SIZES AND LEVELS SHOWN OR REQUIRED. ALLOW FOR FORM CLEARANCE AND FOR PROPER COMPACTION OF REQUIRED BACKFILLING MATERIAL. DAMAGE TO UTILITIES SHALL BE CORRECTED AT THE CONTRACTOR'S EXPENSE.
- EFFECTIVE EROSION PREVENTION AND SEDIMENT CONTROL IS REQUIRED. EROSION CONTROL DEVICES MUST BE INSTALLED AND MAINTAINED MEETING THE LOCAL AGENCY AND STATE AGENCY REQUIREMENTS. THE GOVERNING JURISDICTION MAY, AT ANY TIME, ORDER CORRECTIVE ACTION AND STOPPAGE OF WORK TO ACCOMPLISH EFFECTIVE EROSION CONTROL.
- DRAINAGE SHALL BE CONTROLLED WITHIN THE WORK SITE AND SHALL BE ROUTED SO THAT ADJACENT PRIVATE PROPERTY, PUBLIC PROPERTY, AND THE RECEIVING SYSTEM ARE NOT ADVERSELY IMPACTED. THE ENGINEER AND/OR GOVERNING JURISDICTION MAY, AT ANY TIME, ORDER CORRECTIVE ACTION AND STOPPAGE OF WORK TO ACCOMPLISH EFFECTIVE DRAINAGE CONTROL.
- SITE TOPSOIL STOCKPILED DURING CONSTRUCTION AND USED FOR LANDSCAPING SHALL BE APPROVED BY THE LANDSCAPE ARCHITECT.
- CONTRACTOR TO REVIEW AND CONFIRM GRADES AT JOIN POINTS, SUCH AS AT DAYLIGHT LIMITS AND BUILDING ENTRANCES, PRIOR TO CONSTRUCTION.
- 2% MAXIMUM SLOPE AT ALL ACCESSIBLE PARKING SPACES AND LOADING ZONES.
- 5% MAXIMUM SLOPE (8.33% FOR DESIGNATED RAMPS) AT PEDESTRIAN SIDEWALK CONNECTIONS BETWEEN PUBLIC R.O.W. AND BUILDING ENTRANCES.

UTILITY NOTES

- ALL WORK SHALL CONFORM TO THE CURRENT REQUIREMENTS OF LOCAL AGENCY, THE CURRENT EDITION OF THE UNIFORM PLUMBING CODE, AND THE INTERNATIONAL BUILDING CODE.
- THE WORKING DRAWINGS ARE GENERALLY DIAGRAMMATIC. THEY DO NOT SHOW EVERY OFFSET, BEND OR ELBOW REQUIRED FOR INSTALLATION IN THE SPACE PROVIDED. THEY DO NOT SHOW EVERY DIMENSION, COMPONENT PIECE, SECTION, JOINT OR FITTING REQUIRED TO COMPLETE THE PROJECT. ALL LOCATIONS FOR WORK SHALL BE CHECKED AND COORDINATED WITH EXISTING CONDITIONS IN THE FIELD BEFORE BEGINNING CONSTRUCTION. EXISTING UNDERGROUND UTILITIES LAYING WITHIN THE LIMITS OF EXCAVATION SHALL BE VERIFIED AS TO CONDITION, SIZE AND LOCATION BY UNCOVERING, PROVIDING SUCH IS PERMITTED BY LOCAL PUBLIC AUTHORITIES WITH JURISDICTION, BEFORE BEGINNING CONSTRUCTION. CONTRACTOR TO NOTIFY ENGINEER IF THERE ARE ANY DISCREPANCIES.
- PROVIDE CLEANOUTS AS REQUIRED IN THE CURRENT UNIFORM PLUMBING CODE CHAPTER 7, SECTIONS 707 AND 719, AND CHAPTER 11, SECTION 1101.12. NOTE: NOT ALL REQUIRED CLEANOUTS ARE SHOWN ON THE PLANS.
- ALL STORM PIPING IS DESIGNED USING CONCENTRIC PIPE TO PIPE AND WYE FITTINGS, UNLESS OTHERWISE NOTED.
- ALL DOWNSPOUT LEADERS TO BE 4 INCHES AT 1.0% MINIMUM UNLESS NOTED OTHERWISE.
- VERIFY LOCATION, SIZE AND DEPTH OF EXISTING UTILITIES BY POTHOLING PRIOR TO CONSTRUCTION. NOTIFY ENGINEER OF DISCREPANCIES.
- IF APPLICABLE, PROVIDE 2 INCH PVC DRAIN LINE FROM DOMESTIC WATER METER VAULT AND BACKFLOW PREVENTER VAULT TO THE DOUBLE DETECTOR CHECK VALVE (FIRE) VAULT. PROVIDE 1/3 HP SUMP PUMP AT BASE OF FIRE VAULT AND INSTALL 2 INCH PVC DRAIN LINE WITH BACKFLOW VALVE FROM SUMP PUMP TO DAYLIGHT AT NEAREST CURB. FURNISH 3/4 INCH DIAMETER CONDUIT FROM BUILDING ELECTRICAL ROOM TO FIRE VAULT FOR SUMP PUMP ELECTRICAL SERVICE. NOTE: COORDINATE WITH FIRE PROTECTION CONTRACTOR FOR FLOW SENSOR INSTALLATION AND CONDUIT REQUIREMENTS.
- IF APPLICABLE, CONTRACTOR TO PROVIDE POWER TO IRRIGATION CONTROLLER. SEE LANDSCAPE PLANS AND SPECIFICATIONS.
- SEE BUILDING PLUMBING DRAWINGS FOR PIPING WITHIN THE BUILDING AND UP TO 5 FEET OUTSIDE THE BUILDING, INCLUDING ANY FOUNDATION DRAINAGE PIPING.
- CONTRACTOR TO MAINTAIN MINIMUM 3 FEET OF COVER OVER ALL UTILITY PIPING AND CONDUITS, UNLESS NOTED OTHERWISE.
- WHERE CONNECTING TO AN EXISTING PIPE, AND PRIOR TO ORDERING MATERIALS, THE CONTRACTOR SHALL EXPOSE THE END OF THE EXISTING PIPE TO VERIFY THE LOCATION, SIZE, AND ELEVATION. NOTIFY ENGINEER OF ANY DISCREPANCIES.
- CONTRACTOR SHALL SCOPE ALL PRIVATE ONSITE GRAVITY SYSTEM LINES THAT ARE BEING CONNECTED TO FOR PROPOSED SERVICE. SCOPING SHALL OCCUR A MINIMUM OF 72 HOURS PRIOR TO CONSTRUCTION AND THE ENGINEER SHALL BE NOTIFIED IMMEDIATELY OF ANY DISCREPANCIES WITH AS-BUILT RECORDS/SURVEY FINDINGS OR IF THE EXISTING UTILITIES ARE DAMAGED OR SHOW SIGNS OF SIGNIFICANT DETERIORATION. CONTRACTOR SHALL PROVIDE THE ENGINEER WITH VIDEO RECORDS, ALONG WITH A SKETCH IF THE LOCATIONS DIFFER FROM AS-BUILT PLANS OR SURVEY FINDINGS.
- PRODUCT MATERIAL SUBMITTALS FOR REVIEW BY THE ENGINEER SHALL BE ACCOMPANIED BY A MANUFACTURER'S CERTIFICATION THAT THE PRODUCT IS CAPABLE OF MEETING PERFORMANCE EXPECTATIONS (I.E. - WATERTIGHT, MINIMUM/MAXIMUM BURIAL, PREVENTION OF GROUNDWATER INTRUSION, ETC.) BASED ON THEIR REVIEW OF THE PROJECT PLANS. IN THE ABSENCE OF A MANUFACTURER'S CERTIFICATION, THE GENERAL CONTRACTOR'S REVIEW STAMP SHALL CONSTITUTE THAT THEY HAVE PERFORMED THE NECESSARY REVIEW TO CERTIFY THE PRODUCT'S CONFORMANCE TO PROJECT SPECIFICATIONS AND GENERAL EXPECTATIONS.

EROSION CONTROL NOTES

- HOLD A PRE-CONSTRUCTION MEETING OF PROJECT CONSTRUCTION PERSONNEL THAT INCLUDES THE LOCAL AGENCY INSPECTOR TO DISCUSS EROSION AND SEDIMENT CONTROL MEASURES AND CONSTRUCTION LIMITS.
- EROSION AND SEDIMENT CONTROL MEASURES MUST BE IN PLACE BEFORE ANY LAND IS DISTURBED AND MUST REMAIN IN PLACE AND BE MAINTAINED, REPAIRED, AND PROMPTLY IMPLEMENTED FOLLOWING PROCEDURES ESTABLISHED FOR THE DURATION OF CONSTRUCTION, INCLUDING APPROPRIATE NON-STORMWATER POLLUTION CONTROLS.
- THE EROSION CONTROL DRAWING IS FOR GENERAL GUIDANCE ONLY. THE CONTRACTOR SHALL KEEP THE PLAN CURRENT FOR ALL PHASES OF CONSTRUCTION AND MEET ALL CITY LOCAL AGENCY EROSION/SEDIMENT CONTROL REQUIREMENTS. ALL EROSION CONTROL MEASURES SHALL CONFORM TO THE REQUIREMENTS OF THE AUTHORITY HAVING JURISDICTION, THE PLANS, AND THE PROJECT SPECIFICATIONS.
- CONSTRUCT EROSION CONTROL IN CONJUNCTION WITH ALL CLEARING AND GRADING ACTIVITIES, AND IN SUCH A MANNER AS TO ENSURE THAT SEDIMENT AND SEDIMENT LADEN WATER DO NOT ENTER THE DRAINAGE SYSTEM, ROADWAYS, OR VIOLATE APPLICABLE WATER STANDARDS.
- METHOD OF INSTALLATION FOR SEDIMENT FENCE SHALL NOT CAUSE DAMAGE TO VEGETATED SLOPE EXCEPT AT POINT OF INSTALLATION. SIDECAST MATERIAL SHALL BE KEPT TO A MINIMUM AND SHALL BE TO THE UPHILL SIDE OF THE SEDIMENT FENCE. THE FENCE SHALL BE INSTALLED AT LEAST 4 FEET FROM ADJACENT TREES.
- ALL EROSION CONTROL DEVICES SHALL BE EXAMINED AND REPAIRED AFTER EACH STORM OCCURRENCE, AND INLETS SHALL BE CLEANED OF SEDIMENT WHENEVER NECESSARY.
- HYDROSEED AND MULCH ALL DISTURBED AREAS UPON COMPLETION OF CONSTRUCTION OR AS DIRECTED BY THE INSPECTOR.
- THE CONTRACTOR SHALL LIMIT CONSTRUCTION TRAFFIC TO PAVED AREAS TO PREVENT AND MINIMIZE SEDIMENT TRACKING OFF-SITE. CONTRACTOR SHALL SWEEP OR VACUUM PAVED AREAS IF SEDIMENT ACCUMULATION OCCURS. DO NOT TRACK SEDIMENT TO THE PUBLIC STREET.
- INSTALL TEMPORARY EROSION PREVENTION SUCH AS JUTE NETTING OR GEOTEXTILE ON DISTURBED AREAS STEEPER THAN 4H:1V.
- STAGING AND STOCKPILE AREAS TO BE DETERMINED BY CONTRACTOR AND ADJUSTED TO ACCOMMODATE THE PROGRESS OF CONSTRUCTION.

SITE WORK NOTES

- ALL CURB RADII TO BE 3 FEET UNLESS NOTED OTHERWISE.
- STAIR RISERS TO BE 4 INCH MINIMUM AND 7 INCH MAXIMUM. ALL RISERS TO BE THE SAME HEIGHT, EXCEPT THE BOTTOM RISER MAY VARY BETWEEN THE MINIMUM AND MAXIMUM TO MATCH GRADE.
- GUARDRAIL SHALL BE INSTALLED WHEREVER A PEDESTRIAN WALKING PATH IS WITHIN 36 INCHES OF A VERTICAL DROP OF 30 INCHES OR GREATER. GUARDRAIL SHALL BE 42 INCHES MINIMUM HEIGHT AND MEET THE REQUIREMENTS OF THE LOCAL BUILDING CODE.

ABBREVIATIONS

CL	CENTER LINE	FS	FINISHED SURFACE ELEVATION
PL	PROPERTY LINE	FW	FIRE WATER/FACE OF WALL
AC	ASPHALT CONCRETE	G	GUTTER LINE
BC	BOTTOM OF CURB ELEVATION	GB	GRADE BREAK
BCR	BEGIN CURB RETURN	GR	FINISH ELEVATION OF GROUND
BMP	BEST MANAGEMENT PRACTICE	IE	INVERT ELEVATION
BS	BOTTOM OF STEP ELEVATION	LT	LEFT
BW	BACK OF WALK ELEVATION	ME	MATCH EXISTING ELEVATION
CB	CATCH BASIN	MH	MANHOLE
CI	CAST IRON	MJ	MECHANICAL JOINT
CO	CLEANOUT	OC	ON CENTER
COV	CITY OF VANCOUVER	OSHA	OREGON STATE HEALTH AUTHORITY
CLR	CLEAR	P	ELEVATION OF FINISH PAVEMENT
CVR	COVER	PC	POINT OF CURVATURE
DDCV	DOUBLE DETECTOR CHECK VAVLE	PCC	POINT OF COMPOUND CURVATURE
DI	DUCTILE IRON	PR	PROPOSED
DW	DOMESTIC WATER	PRC	POINT OF REVERSE CURVATURE
ECR	END CURB RETURN	PT	POINT OF TANGENCY
ELEV	ELEVATION	RD	ROOF DRAIN
EP	EDGE OF PAVEMENT	RIM	RIM ELEVATION
ESC	EROSION/SEDIMENT CONTROL	ROW	RIGHT OF WAY
EW	EACH WAY	RSGV	RESILIENT SEAT GATE VALVE
EX	EXISTING	RT	RIGHT
FDC	FIRE DEPARTMENT CONNECTION	SS	SANITARY SEWER
FF	FINISH FLOOR	STA	STATION
FG	FINISHED GRADE ELEVATION	SW	SIDEWALK
FH	FIRE HYDRANT	TC	TOP OF CURB ELEVATION
FI	FIELD INLET	TH	THRESHOLD ELEVATION
FL	FLOWLINE ELEVATION	TS	TOP OF STEP ELEVATION
		TW	TOP OF WALL ELEVATION
		TYP	TYPICAL
		ODOT	OREGON DEPARTMENT OF TRANSPORTATION

PAVEMENT SECTIONS

**FOR REFERENCE ONLY. REFER TO GEOTECHNICAL REPORT FOR MINIMUM REQUIREMENTS
(REPORT OF GEOTECHNICAL SERVICES - "SHERWOOD INDUSTRIAL PARK - PHASE 3 AND 4", BY NV5, DATE JULY 5, 2021)

	CONCRETE DOCK-6" CONCRETE OVER 4" CRUSHED ROCK W/#4 BARS @ 2' O.C. EACH WAY
	CAR PARKING AREA 4.0" AC OVER 9" CRUSHED ROCK
	HEAVY DUTY AREA 5.0" AC OVER 13.0" CRUSHED ROCK

(SEE GEOTECHNICAL REPORT FOR CTB PAVEMENT OPTIONS)

LEGEND

	EXISTING	PROPOSED
RIGHT-OF-WAY LINE	---	---
BOUNDARY LINE	---	---
CENTERLINE	---	---
PROPERTY LINE	---	---
CURB	---	=====
FIRE LANE	---	=====
WETLAND BOUNDARY	---	-----
EDGE OF PAVEMENT	---	---
FENCE LINE	---●---●---●---	---
GRAVEL EDGE	---	---
POWER LINE	---	---
OVERHEAD WIRE	---	---
TRAFFIC SIGNAL WIRE	---	---
TELEPHONE LINE	---	---
TELEVISION LINE	---	---
GAS LINE	---	---
STORM SEWER LINE	---	=====
SANITARY SEWER LINE	---	=====
WATER LINE	---	-----
TREE		
CONTROL MANHOLE		
DRYWELL		
FIRE DEPARTMENT CONNECTION		
FIRE HYDRANT		
WATER BLOWOFF/AIR RELEASE		
WATER METER		
WATER VALVE		
BACKFLOW PREVENTOR		
WATER VAULT		
MONITORING WELL		
STORM/SANITARY MANHOLE		
STORM SEWER CATCH BASIN		
SANITARY CLEAN OUT		
GAS VALVE		
GAS METER		
SIGN		
MAIL BOX		
FOUND SURVEY MONUMENT		
GUY WIRE ANCHOR		
UTILITY POLE		
BOLLARD		
POWER TRANSFORMER		
LIGHT POLE		
VEGETAED COORIDOR		
WETLANDS		
SITE LIGHT		
CONTOUR	115	115

NOTICE TO EXCAVATORS:
ATTENTION: OREGON LAW REQUIRES YOU TO FOLLOW RULES ADOPTED BY THE OREGON UTILITY NOTIFICATION CENTER. THOSE RULES ARE SET FORTH IN OAR 952-001-0010 THROUGH OAR 952-001-0090. YOU MAY OBTAIN COPIES OF THE RULES BY CALLING THE CENTER.
(NOTE: THE TELEPHONE NUMBER FOR THE OREGON UTILITY NOTIFICATION CENTER IS (503)-232-1987).


POTENTIAL UNDERGROUND FACILITY OWNERS

Dig Safely.

Call the Oregon One-Call Center
DIAL 811 or 1-800-332-2344

EMERGENCY TELEPHONE NUMBERS

NW NATURAL GAS
M-F 7am-6pm 503-226-4211 Ext.4313
AFTER HOURS 503-226-4211
PGE 503-464-7777
QWEST 1-800-573-1311
VERIZON 1-800-483-1000



Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknze.com

MACKENZIE.
DESIGN DRIVEN | CLIENT FOCUSED

Client
**ORWA SHERWOOD,
LLC**

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project
**SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)**

© MACKENZIE 2022
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER,
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**EXISTING
CONDITIONS
PLAN**

DRAWN BY:

CHECKED BY:


SHEET:

C1.00

JOB NO. **2200393.00**



MATCH - SEE SHEET 2



UTILITY STATEMENT

THE UNDERGROUND UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND EXISTING DRAWINGS. THE SURVEYOR MAKES NO GUARANTEE THAT THE UNDERGROUND UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UNDERGROUND UTILITIES SHOWN ARE IN THE EXACT LOCATION INDICATED ALTHOUGH HE DOES CERTIFY THAT THEY ARE LOCATED AS ACCURATELY AS POSSIBLE FROM INFORMATION AVAILABLE. THE SURVEYOR HAS NOT PHYSICALLY LOCATED THE UNDERGROUND UTILITIES.

SANITARY SEWER INFORMATION

SS1	MANHOLE RM = 134.36' 12" I.E. IN (W) = 126.8' 12" I.E. IN (SE) = 116.6' 12" I.E. OUT (NW) = 116.3'	SS4	MANHOLE RM = 147.00' 10" I.E. IN (W) = 138.0' 10" I.E. OUT (E) = 137.5'
SS2	MANHOLE RM = 141.58' 12" I.E. IN (SW) = 128.0' 12" I.E. OUT (E) = 127.8'	SS5	MANHOLE RM = 148.52' 10" I.E. IN (S) = 140.0' 10" I.E. OUT (E) = 139.8'
SS3	MANHOLE RM = 138.76' 10" I.E. IN (W) = 132.5' 10" I.E. OUT (NE) = 132.4'	SS6	MANHOLE RM = 151.39' 10" I.E. IN (S) = 140.9' 10" I.E. OUT (N) = 140.8'

STORM SEWER INFORMATION

SD1	MANHOLE RM = 162.24' 12" I.E. IN (SW) = 154.9' 30" I.E. IN (W) = 156.3' 30" I.E. OUT (E) = 153.8'	SD7	PVC OUTFALL 24" I.E. OUT (E) = 140.2'	SD11	CATCH BASIN RM = 148.97' 10" I.E. OUT (SE) = 145.7'
SD2	ROP OUTFALL 18" I.E. OUT (NW) = 139.8'	SD8	MANHOLE RM = 151.17' 15" I.E. IN (W) = 143.9' 18" I.E. IN (N) = 142.8' 24" I.E. IN (S) = 142.5' 24" I.E. OUT (E) = 142.3'	SD12	MANHOLE RM = 154.30' 10" I.E. IN (E) = 148.1' 10" I.E. IN (W) = 148.1' 18" I.E. OUT (S) = 148.0'
SD3	PVC INLET 24" I.E. OUT (NE) = 139.9'	SD9	MANHOLE RM = 148.51' 10" I.E. IN (NE) = 144.1' 10" I.E. IN (NW) = 143.8' 12" I.E. IN (N) = 143.8' 18" I.E. OUT (S) = 143.5'	SD13	CATCH BASIN RM = 153.94' 10" I.E. OUT (W) = 150.8'
SD4	FLOW CONTROL MANHOLE RM = 147.66' 24" I.E. OUT (E) = 139.8'	SD10	CATCH BASIN RM = 148.01' 10" I.E. OUT (NW) = 145.7'	SD14	CATCH BASIN RM = 153.93' 10" I.E. OUT (E) = 150.3'
SD5	MANHOLE RM = 138.93' 24" I.E. IN (W) = 132.6' 24" I.E. OUT (E) = 132.4'				
SD6	PVC OUTFALL 15" I.E. OUT (SE) = 140.8'				

LEGEND

DECIDUOUS TREE
CONIFEROUS TREE
FIRE HYDRANT
WATER METER
WATER VALVE
WATER VAULT
SANITARY SEWER CLEAN OUT
SANITARY SEWER MANHOLE
STORM SEWER CLEAN OUT
STORM SEWER CATCH BASIN
STORM SEWER MANHOLE
GAS MARKER
GAS VALVE
GUY WIRE ANCHOR
UTILITY POLE
POWER VAULT
ELECTRICAL METER
POWER JUNCTION BOX
POWER TRANSFORMER
STREET LIGHT
TELEPHONE/TELEVISION VAULT
TELEPHONE/TELEVISION JUNCTION BOX
TELEPHONE/TELEVISION RISER
MAILBOX
SIGN
FOUND SURVEY MONUMENT

RIGHT-OF-WAY LINE
BOUNDARY LINE
PROPERTY LINE
CENTERLINE
DITCH
CURB
EDGE OF PAVEMENT
EASEMENT
FENCE LINE
GRAVEL EDGE
POWER LINE
OVERHEAD WIRE
TELEPHONE LINE
GAS LINE
STORM SEWER LINE
SANITARY SEWER LINE
WATER LINE
BRUSH LINE

NOTES

- 1) THE FIELD SURVEY FOR THIS MAP WAS COMPLETED ON MARCH 31, 2021.
- 2) ELEVATIONS AND CONTOURS ARE BASED ON WASHINGTON COUNTY BENCHMARK NUMBER 103. THE BENCHMARK IS A 3" BRASS DISK SET IN CONCRETE AT THE SOUTHWEST CORNER OF THE INTERSECTION OF SW TUALATIN-SHERWOOD ROAD AND THE R/R CROSSING, AND HAS AN ELEVATION OF 171.38 FEET ON THE NGVD 1929 DATUM.
- 3) THE BASIS OF BEARINGS FOR THIS SURVEY IS SURVEY NO. 28065.
- 4) THE RIGHT-OF-WAY WIDTHS WERE ESTABLISH USING INFORMATION FROM RECORD SURVEYS AND THE TAX ASSESSOR'S MAP.
- 5) THE EASEMENTS SHOWN ON THIS MAP ARE BASED ON THE TITLE REPORT, PREPARED BY LAWYERS TITLE OF OREGON LLC, WITH ORDER NUMBER 322100068 AND WITH AN EFFECTIVE DATE OF JANUARY 29, 2021 AT 8.00 A.M.
- 6) THE UNDERGROUND UTILITIES ARE BASED ON THE MARKINGS PER LOCATE TICKET NUMBER 21049052.

ORTHWEST SURVEYING, INC.
1815 NW 169th PLACE, SUITE 2090
BEAVERTON, OR 97006
PH: (503) 848-2127 FAX: (503) 848-2179
EMAIL: nwsurveying@nwsi.com

LOCATED IN THE SE 1/4 OF SECTION 29,
TOWNSHIP 2 SOUTH, RANGE 1 WEST, W.M.,
CITY OF SHERWOOD,
WASHINGTON COUNTY, OREGON

TOPOGRAPHIC SURVEY
SHERWOOD INDUSTRIAL PARK
SHERWOOD
OREGON


DRAWING NO.: 2255 TOPO
SCALE: AS NOTED
DRAWING GENERATED BY: LD2004
DRAWN BY: CDW
CHECKED BY: CHS

PREPARED FOR:
ORWA SHERWOOD, LLC
6320 NE HIGHWAY 99E
VANCOUVER, WA 98665

REVISIONS:
INITIAL RELEASE: APR. 16, 2021

JOB NUMBER
2255

SHEET
1 OF 3



Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknze.com

MACKENZIE.
DESIGN DRIVEN | CLIENT FOCUSED

Client
**ORWA SHERWOOD,
LLC**

**8320 NE HIGHWAY 99
VANCOUVER, WA 98665**

SITE DATA (ENTIRE SITE)

ENTIRE SITE AREA	2,148,047	SF	(49.31 AC)	(100%)
SUBJECT SITE AREA	175,001	SF	(4.02 AC)	(8.1%)

SITE DATA (BLDGS 05 - 06)

SUBJECT SITE AREA	175,001	SF	(4.02 AC)	
TOTAL BUILDING FOOTPRINT	19,221	SF	(0.44 AC)	(11.0%)
BUILDING 05 FOOTPRINT	9,027	SF		
BUILDING 06 FOOTPRINT	10,194	SF		
PARKING/DRIVE/LOADING AREA	64,655	SF	(1.48 AC)	(36.9%)
LANDSCAPE AREA	91,125	SF	(2.09 AC)	(52.1%)

PARKING DATA (BLDGS 05 - 06)

STANDARD	105	
ACCESSIBLE	8	
TOTAL PROVIDED	113	(4.75/1,000SF)
REQUIRED PARKING	77	
BIKE PARKING REQUIRED	5	
BIKE PARKING PROVIDED	8	



Project
**SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)**

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date


SHEET TITLE:
**OVERALL SITE
PLAN**

DRAWN BY:
CHECKED BY:
SHEET:

C1.10

JOB NO. **2200393.00**

LAND USE RESUBMITTAL: 1/11/2023
2200393.00\DRAWINGS\CIVIL\1993-C1.10.DWG RLF 01/08/23 13:47 1:100



Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknz.com

MACKENZIE.
DESIGN DRIVEN | CLIENT FOCUSED

Client
**ORWA SHERWOOD,
LLC**

**8320 NE HIGHWAY 99
VANCOUVER, WA 98665**

Project
**SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)**

© MACKENZIE 2022
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER,
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**SITE PLAN
BUILDINGS
5 & 6**

DRAWN BY:
CHECKED BY:
SHEET:

C1.13

JOB NO. **2200393.00**



KEYNOTES

- 32-01 PROPOSED TRASH ENCLOSURE, SEE ARCHITECTURAL PLANS
- 32-02 ACCESSIBLE PARKING STALL PER 4/C5.10
- 32-03 ACCESSIBLE PARKING STALL SIGN PER 4/C5.10
- 32-04 ACCESSIBLE COMPLIANT PERPENDICULAR RAMP PER 6/C5.10
- 32-05 CONCRETE VERTICAL CURB PER 1/C5.10
- 32-06 PARKING STALL STRIPING PER 2/C5.11
- 32-07 INSTALL STOP SIGN
- 32-08 BUMPER OVERHANG
- 32-09 SIDEWALK PER 2/C5.10
- 32-10 RETAINING WALL (MAX. 4')
- 32-11 ACCESSIBLE COMPLIANT PARALLEL RAMP
- 32-12 EXISTING POWER POLE TO BE RELOCATED BY PGE
- 32-13 ASPHALT PAVING SECTION PER 7/C5.10
- 32-14 CONCRETE CROSSWALK
- 32-15 CATCH BASIN, SEE STORMWATER PLANS
- 32-16 FDC, SEE WATER AND SANITARY PLANS
- 32-17 FIRE HYDRANT, SEE WATER AND SANITARY PLANS
- 32-18 WAREHOUSE ACCESS STEM WALL, SEE STRUCTURAL PLANS
- 32-19 WAREHOUSE DRIVE IN ACCESS
- 32-20 PIPE BOLLARD, SEE 3/C5.11
- 32-21 ASPHALT TO CONCRETE TRANSITION, SEE 7/C5.12
- 32-22 PROTECT GUY ANCHORS
- 32-23 PROTECT BPA TOWER (NO GRADING WITHIN 20' OF TOWER, COORDINATE WITH BPA.
- 32-24 ADA ACCESS ROUTE
- 32-25 STAIRWAY PER 6/C5.11
- 32-26 RECONSTRUCTED STORMWATER FACILITY, SEE STORMWATER PLAN
- 32-27 ACCESSIBLE DRIVE AISLE SIGN
- 32-28 EXISTING FIRE HYDRANT
- 32-29 PROPOSED SITE STAIRS
- 32-30 LIMITS OF FLOODPLAIN
- 32-31 VEGETATED COORIDOR
- 32-32 RETAINING WALL (MAX. 10')
- 32-33 BUMPER OVERHANG
- 32-34 FIRE LANE
- 32-35 (4) 2'x6' BIKE PARKING SPACES
- 32-36 PROPOSED SITE LIGHT
- 32-37 PERMANENT SLOPE EASEMENT
- 32-38 TEMPORARY CONSTRUCTION EASEMENT
- 32-39 LOADING ZONE
- 32-40 EXISTING R.O.W.
- 32-41 EXISTING SANITARY SEWER EASEMENT
- 32-42 EXISTING PEDESTRIAN EASEMENT
- 32-43 EXISTING BPA EASEMENT
- 32-44 EXISTING W/O EASEMENT
- 32-45 EXISTING PUBLIC UTILITY EASEMENT
- 32-46 VISION AREA

CURB RADIUS NOTE

ALL CURB RADII 3' UNLESS OTHERWISE NOTED

LAND USE RESUBMITTAL: 1/11/2023





Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknzie.com

MACKENZIE.
DESIGN DRIVEN | CLIENT FOCUSED

Client
**ORWA SHERWOOD,
LLC**

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project
**SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)**

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**FIRE ACCESS
PLAN**

DRAWN BY:



CHECKED BY:

SHEET:

C1.15

JOB NO. **2200393.00**


LAND USE RESUBMITTAL: 1/11/2023



Pumper Fire Truck
Overall Length 40.00ft
Overall Width 8.167ft
Overall Body Height 7.745ft
Min Body Ground Clearance 0.656ft
Track Width 8.167ft
Lock-to-lock time 5.00s
Max Wheel Angle 45.00°

FIRE TRUCK USED






*PRELIMINARY PLAN, FINAL DESIGN TO BE IMPLEMENTED BY CONTRACTOR.
WIRING, CONNECTIONS, POLES, AND LIGHTS TO BE DESIGN-BUILT.

LIGHT USED
LITHONIA DSX0 LED 40C 1000 40K T4M MVOLT HS (DOUBLE)
MOUNTING HEIGHT: 25'

REVISION SCHEDULE		
Delta	Issued As	Issue Date



Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknze.com

MACKENZIE.
DESIGN DRIVEN • CLIENT FOCUSED

Client
**ORWA SHERWOOD,
LLC**

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project
**SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)**

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER,
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**GRADING PLAN
BUILDINGS
5 & 6**



DRAWN BY:

CHECKED BY:

SHEET:

C1.23

JOB NO. **2200393.00**



GRADING PLAN -BUILDINGS 5 & 6

30 0 15 30 60 120
(IN FEET)
1 inch = 30 ft.

NOTICE TO EXCAVATORS:
ATTENTION: OREGON LAW REQUIRES YOU
TO FOLLOW RULES ADOPTED BY THE
OREGON UTILITY NOTIFICATION CENTER.
THOSE RULES ARE SET FORTH IN OAR
952-001-0010 THROUGH OAR
952-001-0090. YOU MAY OBTAIN
COPIES OF THE RULES BY CALLING THE
CENTER.

(NOTE: THE TELEPHONE NUMBER FOR
THE OREGON UTILITY NOTIFICATION
CENTER IS (503)-232-1987).

POTENTIAL UNDERGROUND FACILITY OWNERS

Dig Safely.




Call the Oregon One-Call Center
DIAL 811 or 1-800-332-2344

EMERGENCY TELEPHONE NUMBERS


NW NATURAL GAS
M-F 7am-6pm 503-226-4211 Ext.4313
AFTER HOURS 503-226-4211
PGE 503-464-7777
QWEST 1-800-573-1311
VERIZON 1-800-483-1000

LAND USE RESUBMITTAL: 1/11/2023

220039300 C:\TEMP\AC\PUBLISH_26292\393-C1.21-23.DWG:C1.23 RLF 01/09/23 09:26 1:30



REVISION SCHEDULE		
Delta	Issued As	Issue Date



Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknze.com

MACKENZIE.
DESIGN DRIVEN • CLIENT FOCUSED

Client
**ORWA SHERWOOD,
LLC**

**8320 NE HIGHWAY 99
VANCOUVER, WA 98665**

Project
**SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)**

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER,
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**STORMWATER
PLAN
BUILDINGS
5 & 6**

DRAWN BY:

CHECKED BY:

SHEET:


PRIVATE FACILITY NOTE

ALL STORMWATER FACILITIES INSTALLED ONSITE
TO BE PRIVATELY INSPECTED AND MAINTAINED.

C1.33

JOB NO. **2200393.00**

LAND USE RESUBMITTAL: 1/11/2023



NOTICE TO EXCAVATORS:
ATTENTION: OREGON LAW REQUIRES YOU
TO FOLLOW RULES ADOPTED BY THE
OREGON UTILITY NOTIFICATION CENTER.
THOSE RULES ARE SET FORTH IN OAR
952-001-0010 THROUGH OAR
952-001-0090. YOU MAY OBTAIN
COPIES OF THE RULES BY CALLING THE
CENTER.
(NOTE: THE TELEPHONE NUMBER FOR
THE OREGON UTILITY NOTIFICATION
CENTER IS (503)-232-1987).

POTENTIAL UNDERGROUND FACILITY OWNERS

Dig Safely.

Call the Oregon One-Call Center
DIAL 811 or 1-800-332-2344

EMERGENCY TELEPHONE NUMBERS

NW NATURAL GAS
M-F 7am-6pm 503-226-4211 Ext.4313
AFTER HOURS 503-226-4211
PGE 503-464-7777
QWEST 1-800-573-1311
VERIZON 1-800-483-1000

RESTRAINED JOINT NOTES

TEST PRESSURE: 200 PSI
DEPTH TO BURY: 3 FT
PIPE MATERIAL: PVC
SAFETY FACTOR: 1 TO 1.5
LENGTH OF RESTRAINT: 20 FT
ALONG MAIN ON TEES, Lr:

NOTIFY ENGINEER IF DEVIATING FROM ABOVE SPECIFICATIONS.

LENGTH OF PIPE REQUIRING RESTRAINED JOINTS		
	8" DIA	10" DIA
11 ° BEND	3'	4'
22 ° BEND	6'	8'
45° BENDS	13'	15'
90° BEND	31'	36'
TEE	1'	4'
DEAD ENDS	70'	84'

CITY RETAINS AUTHORITY TO MODIFY AND/OR ADD JOINT RESTRAINTS AT THE DISCRETION OF THE CITY ENGINEER.

M.

Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknzie.com

MACKENZIE.

DESIGN DRIVEN | CLIENT FOCUSED

Client
ORWA SHERWOOD,
LLC

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project
SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER
WITHOUT PRIOR WRITTEN PERMISSION


REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
WATER AND
SANITARY PLAN
BUILDINGS
5 & 6


DRAWN BY:
CHECKED BY:
SHEET:

C1.43

JOB NO. 2200393.00



WATER AND SANITARY PLAN -BUILDINGS 5 & 6



NOTICE TO EXCAVATORS:
ATTENTION: OREGON LAW REQUIRES YOU TO FOLLOW RULES ADOPTED BY THE OREGON UTILITY NOTIFICATION CENTER. THOSE RULES ARE SET FORTH IN OAR 952-001-0010 THROUGH OAR 952-001-0090. YOU MAY OBTAIN COPIES OF THE RULES BY CALLING THE CENTER.
(NOTE: THE TELEPHONE NUMBER FOR THE OREGON UTILITY NOTIFICATION CENTER IS (503)-232-1987).

POTENTIAL UNDERGROUND FACILITY OWNERS

Dig Safely.

Call the Oregon One-Call Center
DIAL 811 or 1-800-332-2344

EMERGENCY TELEPHONE NUMBERS

NW NATURAL GAS
M-F 7am-6pm 503-226-4211 Ext.4313
AFTER HOURS 503-226-4211
PGE 503-464-7777
QWEST 1-800-573-1311
VERIZON 1-800-483-1000

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**CLEARING AND
DEMOLITION
EROSION AND
SEDIMENT
CONTROL PLAN**

DRAWN BY:

CHECKED BY:

SHEET:

C1.51

JOB NO. **2200393.00**

GRADING AND EROSION AND SEDIMENT CONTROL NOTES

- ALL BASE ESC MEASURES (INLET PROTECTION, PERIMETER SEDIMENT CONTROL, GRAVEL CONSTRUCTION ENTRANCES, ETC.) MUST BE IN PLACE, FUNCTIONAL, AND APPROVED IN AN INITIAL INSPECTION, PRIOR TO COMMENCEMENT OF CONSTRUCTION ACTIVITIES.
- SEDIMENT BARRIERS APPROVED FOR USE INCLUDE SEDIMENT FENCE, BERMS CONSTRUCTED OUT OF MULCH, CHIPPINGS, OR OTHER SUITABLE MATERIAL, STRAW WATTLES, OR OTHER APPROVED MATERIALS.
- SENSITIVE RESOURCES INCLUDING, BUT NOT LIMITED TO, TREES, WETLANDS, AND RIPARIAN PROTECTION AREAS SHALL BE CLEARLY DELINEATED WITH ORANGE CONSTRUCTION FENCING OR CHAIN LINK FENCING IN A MANNER THAT IS CLEARLY VISIBLE TO ANYONE IN THE AREA. NO ACTIVITIES ARE PERMITTED TO OCCUR BEYOND THE CONSTRUCTION BARRIER.
- CONSTRUCTION ENTRANCES SHALL BE INSTALLED AT THE BEGINNING OF CONSTRUCTION AND MAINTAINED FOR THE DURATION OF THE PROJECT. ADDITIONAL MEASURES INCLUDING, BUT NOT LIMITED TO, STREET SWEEPING, AND VACUUMING, MAY BE REQUIRED TO INSURE THAT ALL PAVED AREAS ARE KEPT CLEAN FOR DURATION OF THE PROJECT.
- RUN-ON AND RUN-OFF CONTROLS SHALL BE IN PLACE AND FUNCTIONING PRIOT TO BEGINNING SUBSTANTIAL CONSTRUCTION ACTIVITIES. RUN-ON AND RUN-OFF CONTROL MEASURES INCLUDE: SLOPE DRAINS (WITH OUTLET PROTECTION), CHECK DAMS, SURFACE ROUGHENING, AND BANK STABILIZATION.



NOTES TO CONTRACTOR:

- PROVIDE COMBINATION INLET PROTECTION AND BIO BAGS AT ALL DISCOVERED CATCH BASIN AND STORM DRAIN INLETS (TYP) PER DETAIL 1 AND 2 ON SHEET C1.55.
- COORDINATE WITH OWNER TO PROTECT ANY DISCOVERED TREES TO REMAIN WITHIN THE CONSTRUCTION AREAS PER DETAIL 8 ON SHEET C1.55.
- CONSTRUCTION DEWATERING MUST FOLLOW THE NOTES ON SHEET C1.50.

*PRE-DEVELOPED STORM WATER RUN-OFF OF THE EXISTING AREA IS CONVEYED TO AN EXISTING REGIONAL POND AND THEN OUTFLOWS EAST TO EXISTING WETLANDS ONSITE.

EROSION CONTROL LEGEND

CONCRETE WASHOUT	
INLET PROTECTION	
SEDIMENT FENCE	
CONSTRUCTION ENTRANCE	
EXISTING DRAINAGE DIRECTION	
PROPOSED DRAINAGE DIRECTION	
EXISTING CONTOUR	
PROPOSED SUBGRADE CONTOURS	
LIMIT OF DISTURBANCE	



REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**MASS GRADING,
AND
STABILIZATION
CONSTRUCTION
EROSION / SED.
CONTROL PLAN**

DRAWN BY:

CHECKED BY:

SHEET:

GRADING, STREET AND UTILITY EROSION AND SEDIMENT CONSTRUCTION NOTES:

- SEED USED FOR TEMPORARY OR PERMANENT SEEDING SHALL BE COMPOSED OF ONE OF THE FOLLOWING MIXTURES, UNLESS OTHERWISE AUTHORIZED:
 - VEGETATED CORRIDOR AREAS REQUIRE NATIVE SEED MIXES. SEE RESTORATION PLAN FOR APPROPRIATE SEED MIX.
 - DWARF GRASS MIX (MIN. 100 LB./AC.)
 - DWARF PERENNIAL RYEGRASS (80% BY WEIGHT)
 - CREeping RED FESCUE (20% BY WEIGHT)
 - STANDARD HEIGHT GRASS MIX (MIN. 100LB./AC.)
 - ANNUAL RYEGRASS (40% BY WEIGHT)
 - TURF-TYPE FESCUE (60% BY WEIGHT)
- SLOPE TO RECEIVE TEMPORARY OR PERMANENT SEEDING SHALL HAVE THE SURFACE ROUGHENED BY MEANS OF TRACK-WALKING OR THE USE OF OTHER APPROVED IMPLEMENTS. SURFACE ROUGHENING IMPROVES SEED BEDDING AND REDUCES RUN-OFF VELOCITY.
- LONG TERM SLOPE STABILIZATION MEASURES SHALL INCLUDE THE ESTABLISHMENT OF PERMANENT VEGETATIVE COVER VIA SEEDING WITH APPROVED MIX AND APPLICATION RATE.
- TEMPORARY SLOPE STABILIZATION MEASURES SHALL INCLUDE: COVERING EXPOSED SOIL WITH PLASTIC SHEETING, STRAW MULCHING, WOOD CHIPS, OR OTHER APPROVED MEASURES.
- STOCKPILED SOIL OR STRIPPINGS SHALL BE PLACED IN A STABLE LOCATION AND CONFIGURATION, DURING "WET WEATHER" PERIODS. STOCKPILES SHALL BE COVERED WITH PLASTIC SHEETING OR STRAW MULCH. SEDIMENT FENCE IS REQUIRED AROUND THE PERIMETER OF THE STOCKPILE.
- EXPOSED CUT OR FILL AREAS SHALL BE STABILIZED THROUGH THE USE OF TEMPORARY SEEDING AND MULCHING, EROSION CONTROL BLANKETS OR MATS, MID-SLOPE SEDIMENT FENCES OR WATTLES, OR OTHER APPROPRIATE MEASURES. SLOPES EXCEEDING 25% MAY REQUIRE ADDITIONAL EROSION CONTROL MEASURES.
- AREAS SUBJECT TO WIND EROSION SHALL USE APPROPRIATE DUST CONTROL MEASURES INCLUDING THE APPLICATION OF A FINE SPRAY OF WATER, PLASTIC SHEETING, STRAW MULCHING, OR OTHER APPROVED MEASURES.
- CONSTRUCTION ENTRANCES SHALL BE INSTALLED AT THE BEGINNING OF CONSTRUCTION AND MAINTAINED FOR THE DURATION OF THE PROJECT. ADDITIONAL MEASURES INCLUDING, BUT NOT LIMITED TO, TIRE WASHES, STREET SWEEPING, AND VACUUMING MAY BE REQUIRED TO INSURE THAT ALL PAVED AREAS ARE KEPT CLEAN FOR THE DURATION OF THE PROJECT.
- ACTIVE INLETS TO STORM WATER SYSTEMS SHALL BE PROTECTED THROUGH THE USE OF APPROVED INLET PROTECTION MEASURES. ALL INLET PROTECTION MEASURES ARE TO BE REGULARLY INSPECTED AND MAINTAINED AS NEEDED.
- SATURATED MATERIALS THAT ARE HAULED OFF-SITE MUST BE TRANSPORTED IN WATER-TIGHT TRUCKS TO ELIMINATE SPILLAGE OF SEDIMENT AND SEDIMENT-LADEN WATER.

- AN AREA SHALL BE PROVIDED FOR THE WASHING OUT OF CONCRETE TRUCKS IN A LOCATION THAT DOES NOT PROVIDE RUN-OFF THAT CAN ENTER THE STORM WATER SYSTEM, OR SURFACE WATERS. IF THE CONCRETE WASH-OUT AREA CAN NOT BE CONSTRUCTED GREATER THAN 50' FROM ANY DISCHARGE POINT, SECONDARY MEASURES SUCH AS BERMS OR TEMPORARY SETTLING PITS MAY BE REQUIRED. THE WASH-OUT SHALL BE LOCATED WITHIN SIX FEET OF TRUCK ACCESS AND BE CLEANED WHEN IT REACHES 50% OF THE CAPACITY.
- SWEEPINGS FROM EXPOSED AGGREGATE CONCRETE SHALL NOT BE TRANSFERRED TO THE STORM WATER SYSTEM. SWEEPINGS SHALL BE PICKED UP AND DISPOSED IN THE TRASH.
- AVOID PAVING IN WET WEATHER WHEN PAVING CHEMICALS CAN RUN-OFF INTO THE STORM WATER SYSTEM.
- USE BMPs SUCH AS CHECK-DAMS, BERMS, AND INLET PROTECTION TO PREVENT RUN-OFF FROM REACHING DISCHARGE POINTS.
- COVER CATCH BASINS, MANHOLES, AND OTHER DISCHARGE POINTS WHEN APPLYING SEAL COAT, TACK COAT, ETC. TO PREVENT INTRODUCING THESE MATERIALS TO THE STORM WATER SYSTEM.

EROSION CONTROL LEGEND

CONCRETE WASHOUT	
INLET PROTECTION	
SEDIMENT FENCE	
CONSTRUCTION ENTRANCE	
EXISTING DRAINAGE DIRECTION	
PROPOSED DRAINAGE DIRECTION	
EXISTING CONTOUR	
PROPOSED SUBGRADE CONTOURS	
LIMIT OF DISTURBANCE	

DEWATERING NOTE

- CONTRACTOR SHALL MONITOR DEWATERING OPERATIONS WITH DAILY INSPECTION DURING DEWATERING OPERATIONS
- DEWATERING TECHNIQUES SHALL INCLUDE A PUMP AND HOSE TO CONVEY THE DEWATERING FLOW TO APPROVED LOCATIONS. THE APPROVED LOCATIONS ARE THE COMPOST SOCK SEDIMENTATION / FILTRATION BASIN AND STORM DETENTION WATER QUALITY POND
- DEWATERING INTO THE STORM DETENTION WATER QUALITY BASIN MAY ONLY PROCEED ONCE THE DETENTION SYSTEM INLET RIP-RAP AND OUTLET APPURTENANCES AND RIP-RAP OUTFALL ARE INSTALLED AND PERMANENT SOIL STABILIZATION IS IN PLACE.
- TRENCH AND FOUNDATION EXCAVATIONS SHALL BE PROTECTED DURING WET WEATHER FROM OVER SATURATION. THE CONTRACTOR SHALL MONITOR THE COMPOST SOCK BERM BASIN IN-FLOW AND OUT-FLOW RATES AND MODIFY THE SIZE OF THE BERM BASED ON THE FLOW OF DEWATERING.
- DEWATERING OPERATIONS LEFT OVERNIGHT SHALL BE INSPECTED IMMEDIATELY IN THE MORNING. IF DEWATERING OPERATIONS ARE LEFT IN OPERATION OVER WEEKENDS, HOLIDAYS OR MORE THAN 24 HOURS, THE CONTRACTOR SHALL PROVIDE FOR DAILY INSPECTIONS AND PROVIDE FOR INSPECTION WITHIN 2 HOURS AFTER RAIN EVENTS PRODUCING MORE THAN 0.5-INCHES IN A 24-HOUR PERIOD.


*POST-DEVELOPED STORM WATER RUN-OFF OF THE PROPOSED DEVELOPMENT AREA SHEET FLOWS TO AN EXISTING REGIONAL POND BEFORE OUTFLOWING EAST TO EXISTING WETLANDS ONSITE.

EROSION AND SEDIMENT CONTROL BMP IMPLEMENTATION

- ALL BASE ESC MEASURES (INLET PROTECTION, PERIMETER SEDIMENT CONTROL, GRAVEL CONSTRUCTION ENTRANCES, ETC.) MUST BE IN PLACE, FUNCTIONAL, AND APPROVED IN AN INITIAL INSPECTION, PRIOR TO COMMENCEMENT OF CONSTRUCTION ACTIVITIES.
- ALL "SEDIMENT BARRIERS" (TO BE INSTALLED AFTER GRADING) SHALL BE INSTALLED IMMEDIATELY FOLLOWING ESTABLISHMENT OF FINISHED GRADE AS SHOWN ON THESE PLANS.
- LONG TERM SLOPE STABILIZATION MEASURES "INCLUDING MATTING" SHALL BE IN PLACE OVER ALL EXPOSED SOILS AND IMMEDIATELY AFTER GRADING IS COMPLETE.
- THE STORM WATER FACILITY SHALL BE CONSTRUCTED AND LANDSCAPED PRIOR TO THE STORM WATER SYSTEM FUNCTIONING AND SITE PAVING.
- INLET PROTECTION SHALL BE IN-PLACE IMMEDIATELY FOLLOWING PAVING ACTIVITIES.

CUT-FILL

CUT: X CU. YD.
FILL: X CU. YD.
NET: X CU. YD.



MASS GRADING, AND STABILIZATION CONSTRUCTION EROSION / SED. CONTROL PLAN

60 0 30 60 120 240
(IN FEET)
1 inch = 60 ft.

C1.52

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
UTILITY
CONSTRUCTION
EROSION / SED.
CONTROL PLAN

DRAWN BY:
CHECKED BY:
SHEET:

GRADING, STREET AND UTILITY EROSION AND SEDIMENT CONSTRUCTION NOTES:

- SEED USED FOR TEMPORARY OR PERMANENT SEEDING SHALL BE COMPOSED OF ONE OF THE FOLLOWING MIXTURES, UNLESS OTHERWISE AUTHORIZED:
 - VEGETATED CORRIDOR AREAS REQUIRE NATIVE SEED MIXES. SEE RESTORATION PLAN FOR APPROPRIATE SEED MIXES.
 - DWARF GRASS MIX (MIN. 100 LB./AC.)
 - DWARF PERENNIAL RYEGRASS (80% BY WEIGHT)
 - CREEPING RED FESCUE (20% BY WEIGHT)
 - STANDARD HEIGHT GRASS MIX (MIN. 100LB./AC.)
 - ANNUAL RYEGRASS (40% BY WEIGHT)
 - TURF-TYPE FESCUE (60% BY WEIGHT)
- SLOPE TO RECEIVE TEMPORARY OR PERMANENT SEEDING SHALL HAVE THE SURFACE ROUGHENED BY MEANS OF TRACK-WALKING OR THE USE OF OTHER APPROVED IMPLEMENTS. SURFACE ROUGHENING IMPROVES SEED BEDDING AND REDUCES RUN-OFF VELOCITY.
- LONG TERM SLOPE STABILIZATION MEASURES SHALL INCLUDE THE ESTABLISHMENT OF PERMANENT VEGETATIVE COVER VIA SEEDING WITH APPROVED MIX AND APPLICATION RATE.
- TEMPORARY SLOPE STABILIZATION MEASURES SHALL INCLUDE: COVERING EXPOSED SOIL WITH PLASTIC SHEETING, STRAW MULCHING, WOOD CHIPS, OR OTHER APPROVED MEASURES.
- STOCKPILED SOIL OR STRIPPINGS SHALL BE PLACED IN A STABLE LOCATION AND CONFIGURATION, DURING "WET WEATHER" PERIODS. STOCKPILES SHALL BE COVERED WITH PLASTIC SHEETING OR STRAW MULCH. SEDIMENT FENCE IS REQUIRED AROUND THE PERIMETER OF THE STOCKPILE.
- EXPOSED CUT OR FILL AREAS SHALL BE STABILIZED THROUGH THE USE OF TEMPORARY SEEDING AND MULCHING, EROSION CONTROL BLANKETS OR MATS, MID-SLOPE SEDIMENT FENCES OR WATTLES, OR OTHER APPROPRIATE MEASURES. SLOPES EXCEEDING 25% MAY REQUIRE ADDITIONAL EROSION CONTROL MEASURES.
- AREAS SUBJECT TO WIND EROSION SHALL USE APPROPRIATE DUST CONTROL MEASURES INCLUDING THE APPLICATION OF A FINE SPRAY OF WATER, PLASTIC SHEETING, STRAW MULCHING, OR OTHER APPROVED MEASURES.
- CONSTRUCTION ENTRANCES SHALL BE INSTALLED AT THE BEGINNING OF CONSTRUCTION AND MAINTAINED FOR THE DURATION OF THE PROJECT. ADDITIONAL MEASURES INCLUDING, BUT NOT LIMITED TO, TIRE WASHES, STREET SWEEPING, AND VACUUMING MAY BE REQUIRED TO INSURE THAT ALL PAVED AREAS ARE KEPT CLEAN FOR THE DURATION OF THE PROJECT.
- ACTIVE INLETS TO STORM WATER SYSTEMS SHALL BE PROTECTED THROUGH THE USE OF APPROVED INLET PROTECTION MEASURES. ALL INLET PROTECTION MEASURES ARE TO BE REGULARLY INSPECTED AND MAINTAINED AS NEEDED.
- SATURATED MATERIALS THAT ARE HAULED OFF-SITE MUST BE TRANSPORTED IN WATER-TIGHT TRUCKS TO ELIMINATE SPILLAGE OF SEDIMENT AND SEDIMENT-LADEN WATER.

- AN AREA SHALL BE PROVIDED FOR THE WASHING OUT OF CONCRETE TRUCKS IN A LOCATION THAT DOES NOT PROVIDE RUN-OFF THAT CAN ENTER THE STORM WATER SYSTEM, OR SURFACE WATERS. IF THE CONCRETE WASH-OUT AREA CAN NOT BE CONSTRUCTED GREATER THAN 50' FROM ANY DISCHARGE POINT, SECONDARY MEASURES SUCH AS BERMS OR TEMPORARY SETTLING PITS MAY BE REQUIRED. THE WASH-OUT SHALL BE LOCATED WITHIN SIX FEET OF TRUCK ACCESS AND BE CLEANED WHEN IT REACHES 50% OF THE CAPACITY.
- SWEEPINGS FROM EXPOSED AGGREGATE CONCRETE SHALL NOT BE TRANSFERRED TO THE STORM WATER SYSTEM. SWEEPINGS SHALL BE PICKED UP AND DISPOSED IN THE TRASH.
- AVOID PAVING IN WET WEATHER WHEN PAVING CHEMICALS CAN RUN-OFF INTO THE STORM WATER SYSTEM.
- USE BMPs SUCH AS CHECK-DAMS, BERMS, AND INLET PROTECTION TO PREVENT RUN-OFF FROM REACHING DISCHARGE POINTS.
- COVER CATCH BASINS, MANHOLES, AND OTHER DISCHARGE POINTS WHEN APPLYING SEAL COAT, TACK COAT, ETC. TO PREVENT INTRODUCING THESE MATERIALS TO THE STORM WATER SYSTEM.

EROSION CONTROL LEGEND

- CONCRETE WASHOUT
- INLET PROTECTION
- SEDIMENT FENCE
- CONSTRUCTION ENTRANCE
- DRAINAGE FLOW DIRECTION
- EXISTING CONTOUR
- PROPOSED SUBGRADE CONTOURS
- LIMIT OF DISTURBANCE

DEWATERING NOTE


- CONTRACTOR SHALL MONITOR DEWATERING OPERATIONS WITH DAILY INSPECTION DURING DEWATERING OPERATIONS
- DEWATERING TECHNIQUES SHALL INCLUDE A PUMP AND HOSE TO CONVEY THE DEWATERING FLOW TO APPROVED LOCATIONS. THE APPROVED LOCATIONS ARE THE COMPOST SOCK SEDIMENTAION / FILTRATION BASIN AND STORM DETENTION WATER QUALITY POND
- DEWATERING INTO THE STORM DETENTION WATER QUALITY BASIN MAY ONLY PROCEED ONCE THE DETENTION SYSTEM INLET RIP-RAP AND OUTLET APPURTENANCES AND RIP-RAP OUTFALL ARE INSTALLED AND PERMANENT SOIL STABILIZATION IS IN PLACE.
- TRENCH AND FOUNDATION EXCAVATIONS SHALL BE PROTECTED DURING WET WEATHER FROM OVER SATURATION. THE CONTRACTOR SHALL MONITOR THE COMPOST SOCK BERM BASIN IN-FLOW AND OUT-FLOW RATES AND MODIFY THE SIZE OF THE BERM BASED ON THE FLOW OF DEWATERING.
- DEWATERING OPERATIONS LEFT OVERNIGHT SHALL BE INSPECTED IMMEDIATELY IN THE MORNING. IF DEWATERING OPERATIONS ARE LEFT IN OPERATION OVER WEEKENDS, HOLIDAYS OR MORE THAN 24 HOURS, THE CONTRACTOR SHALL PROVIDE FOR DAILY INSPECTIONS AND PROVIDE FOR INSPECTION WITHIN 2 HOURS AFTER RAIN EVENTS PRODUCING MORE THAN 0.5-INCHES IN A 24-HOUR PERIOD.

*POST-DEVELOPED STORM WATER RUN-OFF OF THE PROPOSED DEVELOPMENT AREA COLLECTS INTO CATCH BASINS AND IS CONVEYED TO AN EXISTING REGIONAL POND BEFORE OUTFLOWING EAST TO EXISTING WETLANDS ONSITE.

EROSION AND SEDIMENT CONTROL BMP IMPLEMENTATION

- ALL BASE ESC MEASURES (INLET PROTECTION, PERIMETER SEDIMENT CONTROL, GRAVEL CONSTRUCTION ENTRANCES, ETC.) MUST BE IN PLACE, FUNCTIONAL, AND APPROVED IN AN INITIAL INSPECTION, PRIOR TO COMMENCEMENT OF CONSTRUCTION ACTIVITIES.
- ALL "SEDIMENT BARRIERS" (TO BE INSTALLED AFTER GRADING) SHALL BE INSTALLED IMMEDIATELY FOLLOWING ESTABLISHMENT OF FINISHED GRADE AS SHOWN ON THESE PLANS.
- LONG TERM SLOPE STABILIZATION MEASURES "INCLUDING MATTING" SHALL BE IN PLACE OVER ALL EXPOSED SOILS AND IMMEDIATELY AFTER GRADING IS COMPLETE.
- THE STORM WATER FACILITY SHALL BE CONSTRUCTED AND LANDSCAPED PRIOR TO THE STORM WATER SYSTEM FUNCTIONING AND SITE PAVING.
- INLET PROTECTION SHALL BE IN-PLACE IMMEDIATELY FOLLOWING PAVING ACTIVITIES.

NOT PART
OF APPLICATION



REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**FOUNDATION
PLAN
EROSION/SED.
CONTROL PLAN**

DRAWN BY:

CHECKED BY:


SHEET:

GRADING, STREET AND UTILITY EROSION AND SEDIMENT CONSTRUCTION NOTES:

- SEED USED FOR TEMPORARY OR PERMANENT SEEDING SHALL BE COMPOSED OF ONE OF THE FOLLOWING MIXTURES, UNLESS OTHERWISE AUTHORIZED:
 - VEGETATED CORRIDOR AREAS REQUIRE NATIVE SEED MIXES. SEE RESTORATION PLAN FOR APPROPRIATE SEED MIX.
 - DWARF GRASS MIX (MIN. 100 LB./AC.)
 - DWARF PERENNIAL RYEGRASS (80% BY WEIGHT)
 - CREEPING RED FESCUE (20% BY WEIGHT)
 - STANDARD HEIGHT GRASS MIX (MIN. 100LB./AC.)
 - ANNUAL RYEGRASS (40% BY WEIGHT)
 - TURF-TYPE FESCUE (60% BY WEIGHT)
- SLOPE TO RECEIVE TEMPORARY OR PERMANENT SEEDING SHALL HAVE THE SURFACE ROUGHENED BY MEANS OF TRACK-WALKING OR THE USE OF OTHER APPROVED IMPLEMENTS. SURFACE ROUGHENING IMPROVES SEED BEDDING AND REDUCES RUN-OFF VELOCITY.
- LONG TERM SLOPE STABILIZATION MEASURES SHALL INCLUDE THE ESTABLISHMENT OF PERMANENT VEGETATIVE COVER VIA SEEDING WITH APPROVED MIX AND APPLICATION RATE.
- TEMPORARY SLOPE STABILIZATION MEASURES SHALL INCLUDE: COVERING EXPOSED SOIL WITH PLASTIC SHEETING, STRAW MULCHING, WOOD CHIPS, OR OTHER APPROVED MEASURES.
- STOCKPILED SOIL OR STRIPPINGS SHALL BE PLACED IN A STABLE LOCATION AND CONFIGURATION, DURING "WET WEATHER" PERIODS. STOCKPILES SHALL BE COVERED WITH PLASTIC SHEETING OR STRAW MULCH. SEDIMENT FENCE IS REQUIRED AROUND THE PERIMETER OF THE STOCKPILE.
- EXPOSED CUT OR FILL AREAS SHALL BE STABILIZED THROUGH THE USE OF TEMPORARY SEEDING AND MULCHING, EROSION CONTROL BLANKETS OR MATS, MID-SLOPE SEDIMENT FENCES OR WATTLES, OR OTHER APPROPRIATE MEASURES. SLOPES EXCEEDING 25% MAY REQUIRE ADDITIONAL EROSION CONTROL MEASURES.
- AREAS SUBJECT TO WIND EROSION SHALL USE APPROPRIATE DUST CONTROL MEASURES INCLUDING THE APPLICATION OF A FINE SPRAY OF WATER, PLASTIC SHEETING, STRAW MULCHING, OR OTHER APPROVED MEASURES.
- CONSTRUCTION ENTRANCES SHALL BE INSTALLED AT THE BEGINNING OF CONSTRUCTION AND MAINTAINED FOR THE DURATION OF THE PROJECT. ADDITIONAL MEASURES INCLUDING, BUT NOT LIMITED TO, TIRE WASHES, STREET SWEEPING, AND VACUUMING MAY BE REQUIRED TO INSURE THAT ALL PAVED AREAS ARE KEPT CLEAN FOR THE DURATION OF THE PROJECT.
- ACTIVE INLETS TO STORM WATER SYSTEMS SHALL BE PROTECTED THROUGH THE USE OF APPROVED INLET PROTECTION MEASURES. ALL INLET PROTECTION MEASURES ARE TO BE REGULARLY INSPECTED AND MAINTAINED AS NEEDED.
- SATURATED MATERIALS THAT ARE HAULED OFF-SITE MUST BE TRANSPORTED IN WATER-TIGHT TRUCKS TO ELIMINATE SPILLAGE OF SEDIMENT AND SEDIMENT-LADEN WATER.

- AN AREA SHALL BE PROVIDED FOR THE WASHING OUT OF CONCRETE TRUCKS IN A LOCATION THAT DOES NOT PROVIDE RUN-OFF THAT CAN ENTER THE STORM WATER SYSTEM, OR SURFACE WATERS. IF THE CONCRETE WASH-OUT AREA CAN NOT BE CONSTRUCTED GREATER THAN 50' FROM ANY DISCHARGE POINT, SECONDARY MEASURES SUCH AS BERMS OR TEMPORARY SETTLING PITS MAY BE REQUIRED. THE WASH-OUT SHALL BE LOCATED WITHIN SIX FEET OF TRUCK ACCESS AND BE CLEANED WHEN IT REACHES 50% OF THE CAPACITY.
- SWEEPINGS FROM EXPOSED AGGREGATE CONCRETE SHALL NOT BE TRANSFERRED TO THE STORM WATER SYSTEM. SWEEPINGS SHALL BE PICKED UP AND DISPOSED IN THE TRASH.
- AVOID PAVING IN WET WEATHER WHEN PAVING CHEMICALS CAN RUN-OFF INTO THE STORM WATER SYSTEM.
- USE BMPs SUCH AS CHECK-DAMS, BERMS, AND INLET PROTECTION TO PREVENT RUN-OFF FROM REACHING DISCHARGE POINTS.
- COVER CATCH BASINS, MANHOLES, AND OTHER DISCHARGE POINTS WHEN APPLYING SEAL COAT, TACK COAT, ETC. TO PREVENT INTRODUCING THESE MATERIALS TO THE STORM WATER SYSTEM.

EROSION CONTROL LEGEND



DEWATERING NOTE


- CONTRACTOR SHALL MONITOR DEWATERING OPERATIONS WITH DAILY INSPECTION DURING DEWATERING OPERATIONS
- DEWATERING TECHNIQUES SHALL INCLUDE A PUMP AND HOSE TO CONVEY THE DEWATERING FLOW TO APPROVED LOCATIONS. THE APPROVED LOCATIONS ARE THE COMPOST SOCK SEDIMENTAION / FILTRATION BASIN AND STORM DETENTION WATER QUALITY POND
- DEWATERING INTO THE STORM DETENTION WATER QUALITY BASIN MAY ONLY PROCEED ONCE THE DETENTION SYSTEM INLET RIP-RAP AND OUTLET APPURTENANCES AND RIP-RAP OUTFALL ARE INSTALLED AND PERMANENT SOIL STABILIZATION IS IN PLACE.
- TRENCH AND FOUNDATION EXCAVATIONS SHALL BE PROTECTED DURING WET WEATHER FROM OVER SATURATION. THE CONTRACTOR SHALL MONITOR THE COMPOST SOCK BERM BASIN IN-FLOW AND OUT-FLOW RATES AND MODIFY THE SIZE OF THE BERM BASED ON THE FLOW OF DEWATERING.
- DEWATERING OPERATIONS LEFT OVERNIGHT SHALL BE INSPECTED IMMEDIATELY IN THE MORNING. IF DEWATERING OPERATIONS ARE LEFT IN OPERATION OVER WEEKENDS, HOLIDAYS OR MORE THAN 24 HOURS, THE CONTRACTOR SHALL PROVIDE FOR DAILY INSPECTIONS AND PROVIDE FOR INSPECTION WITHIN 2 HOURS AFTER RAIN EVENTS PRODUCING MORE THAN 0.5-INCHES IN A 24-HOUR PERIOD.

*POST-DEVELOPED STORM WATER RUN-OFF OF THE PROPOSED DEVELOPMENT AREA COLLECTS INTO CATCH BASINS AND IS CONVEYED TO AN EXISTING REGIONAL POND BEFORE OUTFLOWING EAST TO EXISTING WETLANDS ONSITE.

EROSION AND SEDIMENT CONTROL BMP IMPLEMENTATION

- ALL BASE ESC MEASURES (INLET PROTECTION, PERIMETER SEDIMENT CONTROL, GRAVEL CONSTRUCTION ENTRANCES, ETC.) MUST BE IN PLACE, FUNCTIONAL, AND APPROVED IN AN INITIAL INSPECTION, PRIOR TO COMMENCEMENT OF CONSTRUCTION ACTIVITIES.
- ALL "SEDIMENT BARRIERS" (TO BE INSTALLED IMMEDIATELY FOLLOWING ESTABLISHMENT OF FINISHED GRADE AS SHOWN ON THESE PLANS.
- LONG TERM SLOPE STABILIZATION MEASURES "INCLUDING MATTING" SHALL BE IN PLACE OVER ALL EXPOSED SOILS AND IMMEDIATELY AFTER GRADING IS COMPLETE.
- THE STORM WATER FACILITY SHALL BE CONSTRUCTED AND LANDSCAPED PRIOR TO THE STORM WATER SYSTEM FUNCTIONING AND SITE PAVING.
- INLET PROTECTION SHALL BE IN-PLACE IMMEDIATELY FOLLOWING PAVING ACTIVITIES.

NOT PART
OF APPLICATION




- NOTES:
1. THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHT-OF-WAYS. THIS MAY REQUIRE TOP DRESSING, REPAIR AND/OR CLEAN OUT OF ANY MEASURES USED TO TRAP SEDIMENT.
 2. WHEN NECESSARY, WHEELS SHALL BE CLEANED PRIOR TO ENTRANCE ONTO PUBLIC RIGHT-OF- WAY.
 3. WHEN WASHING IS REQUIRED, IT SHALL BE DONE ON AN AREA STABILIZED WITH CRUSHED STONE THAT DRAINS INTO AN APPROVED SEDIMENT TRAP OR SEDIMENT BASIN.
 4. WHERE RUNOFF CONTAINING SEDIMENT LADEN WATER IS LEAVING THE SITE VIA THE CONSTRUCTION ENTRANCE, OTHER MEASURES SHALL BE IMPLEMENTED TO DIVERT RUNOFF THROUGH AN APPROVED FILTERING SYSTEM.
 5. DIMENSIONS
SINGLE FAMILY:
20' LONG BY 20' WIDE 8" DEEP OF ¾" MINUS CLEAN ROCK.
COMMERCIAL/SITE DEVELOPMENT:
50' LONG BY 20' WIDE 3-6" CLEAN ROCK, GOVERNING AUTHORITY MAY REQUIRE GEOTEXTILE FABRIC TO PREVENT SUB-SOIL PUMPING.

CONSTRUCTION ENTRANCE

DRAWING NO. 855


REVISED 10-31-19



SEDIMENT FENCE

DRAWING NO. 875


REVISED 10-31-19



CONCRETE WASHOUT

DRAWING NO. 900


REVISED 10-31-19



INLET PROTECTION TYPE 4

DRAWING NO. 915

REVISED 10-31-19



NOTE:


1. RECESSED CURB INLET CATCH BASINS MUST BE BLOCKED WHEN USING FILTER FABRIC INLET SACKS. SIZE OF FILTER FABRIC INLET SACKS TO BE DETERMINED BY MANUFACTURER.

FOR FURTHER INFORMATION ON DESIGN CRITERIA SEE CHAPTER 4 OF CLEAN WATER SERVICES EROSION PREVENTION AND SEDIMENT CONTROL PLANNING AND DESIGN MANUAL.

INLET PROTECTION TYPE 5

DRAWING NO. 920


REVISED 10-31-19



SEDIMENT BAG

DRAWING NO. 950

REVISED 10-31-19



Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknzie.com

MACKENZIE
DESIGN DRIVEN | CLIENT FOCUSED

Client
ORWA SHERWOOD,
LLC

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project
SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)

© MACKENZIE 2022
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER,
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date


SHEET TITLE:
EROSION AND
SEDIMENT
CONTROL
DETAILS

DRAWN BY:
CHECKED BY:
SHEET:

C1.55


JOB NO. 2200393.00

LAND USE RESUBMITTAL: 1/11/2023




KEYNOTES:

1. CONCRETE FOR CURBING PER PROJECT SPECIFICATIONS
2. PAVEMENT SECTION PER CIVIL PLANS
3. SEE PLANS FOR IMPROVEMENTS AT BACK OF CURB. WHERE SIDEWALK OCCURS, THE SIDEWALK AND TOP OF CURB SHALL BE FLUSH. WHERE ABUTTING A PLANTER AREA, THE FINAL GRADE SHALL BE 1" MINIMUM BELOW TOP OF CURB, OR AS DIRECTED BY THE LANDSCAPE ARCHITECT




NOTES:

- A. CONCRETE SIDEWALK SHALL BE BROOM FINISHED UNLESS OTHERWISE NOTED ON PLANS
- B. SEE PROJECT SPECIFICATIONS FOR CONCRETE, AGGREGATE BASE, AND JOINT MATERIALS
- C. WHERE SIDEWALK ABUTS CURBING, SURFACE SHALL BE FLUSH WITH TOP OF CURB UNLESS NOTED OTHERWISE ON PLANS. WHERE SIDEWALK ABUTS LANDSCAPE OR OTHER PERVIOUS AREA, GRADE SHALL BE RECESSED 1" MINIMUM OR AS OTHERWISE DICTATED BY THE LANDSCAPE ARCHITECT OR NOTED ON PROJECT PLANS
- D. DO NOT USE SHINERS ON TOOLED EDGES UNLESS NOTED OTHERWISE
- E. CONTROL JOINTS SHALL BE EVENLY SPACED AND LOCATED EVERY 5' MAXIMUM, WITH EXPANSION JOINTS EVERY FOURTH JOINT, OR PER PLAN. SIDEWALK JOINTS SHALL BE ALIGNED WITH CURB JOINTS OR WHERE PERPENDICULAR CURBING INTERSECTS.



CONTROL JOINT




EXPANSION JOINT

1 VERTICAL CURB

C5.10

NTS

6" TO FACE OF SIGN



KEYNOTES:


1. 4" WIDE WHITE STRIPE
2. WHITE RETROREFLECTIVE PAVEMENT MARKING SYMBOL (FHWA 3B-22) WITH BLUE RETROREFLECTIVE BACKGROUND (41" TALL x 36" WIDE WITH 4" STROKE WIDTH). OFFSET BACKGROUND LIMIT 4" FROM SYMBOL
3. SEE 5/C5.10 FOR PROPOSED PARALLEL CURB RAMP TO ACCOMMODATE ACCESSIBLE PARKING STALL ACCESS
4. ACCESSIBLE PARKING SPACE SIGNAGE PER DETAIL HEREON. MAINTAIN 48" CLEAR ACCESS AROUND SIGN. INSURE NO INTERFERENCE WITH PARKING STALL OVERHANG

NOTE: MORE DETAIL ON THE FHWA SYMBOL NUMBER REFERENCES HEREON MAY BE FOUND IN THE STANDARD HIGHWAY SIGNS BOOK PUBLISHED BY THE FEDERAL HIGHWAY ADMINISTRATION (FHWA), LATEST EDITION

2 CONCRETE SIDEWALK AND JOINTS

C5.10

NTS




ODOT SIGN NO. R7-8
BACKGROUND: WHITE, RETRO-REFLECTIVE SHEETING
LEGEND: GREEN, RETRO-REFLECTIVE SHEETING
SYMBOL: BLUE RETRO-REFLECTIVE SHEETING ON WHITE RETRO-REFLECTIVE BACKGROUND

ODOT SIGN NO. R7-8A
(WHERE CALLED OUT ON PLANS)
BACKGROUND: WHITE, RETRO-REFLECTIVE SHEETING
LEGEND: GREEN, NON-REFLECTIVE SHEETING
NOTE: ACCESS AISLE FOR SINGLE VAN ACCESSIBLE STALL TO BE LOCATED ON THE PASSENGER'S SIDE


2"x2" SQUARE PERFORATED GALVANIZED
12GA METAL SIGN POST. FOR FURTHER
INFORMATION, SEE DETAIL 1/C5.11

CONCRETE FOUNDATION, ROUND
TOP TO SHED
FINISHED GROUND

NOTE: MORE DETAIL ON THE WSDOT SIGN/SYMBOL
NUMBER REFERENCES HEREON MAY BE FOUND IN
THE SIGN FABRICATION MANUAL PUBLISHED BY
THE WASHINGTON STATE DEPARTMENT OF
TRANSPORTATION (WSDOT), LATEST EDITION



HALF TYPE




FULL TYPE

3 NOT USED


C5.10

N.T.S.

1:1



ISOMETRIC - HALF TYPE




LEGEND
TURNING SPACE/LANDING
MAX 2.0% FINISHED
SLOPE IN ALL DIRECTIONS*

SLOPE 1.5% MAX*
(MAX 2.0% FINISHED
SURFACE SLOPE)

SLOPE 7.5% MAX*
(MAX 8.3% FINISHED
SLOPE)

*SLOPES GOVERN OVER ELEVATIONS




ISOMETRIC - FULL TYPE


4 ACCESSIBLE PARKING STALL

C5.10

NTS



WINGED TYPE




SQUARE TYPE

LEGEND
TURNING SPACE/LANDING
MAX 2.0% FINISHED
SLOPE IN ALL DIRECTIONS*


SLOPE 1.5% MAX*
(MAX 2.0% FINISHED
SURFACE SLOPE)

SLOPE 7.5% MAX*
(MAX 8.3% FINISHED
SLOPE)

*SLOPES GOVERN OVER ELEVATIONS



ISOMETRIC - WINGED TYPE




ISOMETRIC - SQUARE TYPE


5 PARALLEL CURB RAMPS

C5.10

NTS



LIGHT DUTY (PARKING)




HEAVY DUTY

KEYNOTES:


1. ASPHALT PAVEMENT SECTION PER PROJECT SPECIFICATIONS
2. CRUSHED ROCK BASE SECTION PER PROJECT SPECIFICATIONS
3. COMPACTED SUBGRADE PER GEOTECHNICAL RECOMMENDATIONS

NOTES:

- A. SEE PLANS FOR LOCATIONS OF LIGHT AND HEAVY DUTY PAVEMENTS. IF NONE SPECIFIED, USE LIGHT DUTY IN PASSENGER VEHICLE PARKING STALLS ONLY AND HEAVY DUTY IN ALL OTHER LOCATIONS
- B. SEE PROJECT GEOTECHNICAL REPORT FOR PAVEMENT AND SUBGRADE PREPARATION RECOMMENDATIONS



TRUNCATED DOME DETAIL



TRUNCATED DOME PANEL

NOTES:

- A. PLACE TRUNCATED DOME DETECTABLE WARNING TEXTURE (OR CAST-IN-PLACE PANELS) IN THE LOWER 24" FOR THE FULL WIDTH OF THE RAMP
- B. ARRANGE DOMES USING AN INLINE PATTERN AS SHOWN IN THE DETAIL ABOVE
- C. COLOR OF DOME TEXTURE (OR PANELS) TO BE SAFETY YELLOW, UNLESS NOTED OTHERWISE ON PLANS
- D. SURFACE APPLIED PANELS SHALL ONLY BE ALLOWED IN RETROFIT CONDITIONS AND WITH THE PRIOR APPROVAL OF THE ENGINEER

6 PERPENDICULAR CURB RAMPS

C5.10

NTS



ISOMETRIC - WINGED TYPE



ISOMETRIC - SQUARE TYPE

7 ASPHALT PAVEMENT SECTION

C5.10

NTS






8 TRUNCATED DOMES

C5.10

NTS







REVISION SCHEDULE		
Delta	Issued As	Issue Date



COMPACT CARPOOL

COMMON PARKING STALL DESIGNATIONS







1 SIGN POST

NTS




2 PARKING STALL STRIPING

NTS



5 CONCRETE STAIR

NTS






7 FLOW CONTROL MANHOLE

NTS



3 6" PIPE BOLLARD

NTS



6 UTILITY TRENCH BEDDING & BACKFILL

NTS




8 SHEAR GATE

NTS

[illegible]

REVISION SCHEDULE		
Delta	Issued As	Issue Date




1

PRIVATE SEWER CLEANOUT

C5.12

N.T.S.




2

LANDSCAPE AREA DRAIN

C5.12

NTS




3

PIPE OUTFALL - RIP RAP

C5.12

NTS



4

FIRE DEPARTMENT CONNECTION

C5.12

NTS

5

NOT USED

C5.12

N.T.S.

6

NOT USED

C5.12


N.T.S.

7

ASPHALT TO CONCRETE TRANSITION

C5.12

NTS





8

STORM SEWER MANHOLES

C5.12

NTS




9

STEEL CATCH BASIN

C5.12

NTS



REVISION SCHEDULE		
Delta	Issued As	Issue Date








SHEET TITLE:

STORMWATER DETAILS

DRAWN BY:

CHECKED BY:

SHEET:



REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
CITY OF
SHERWOOD
STANDARD
DETAILS





DRAWN BY:
CHECKED BY:
SHEET:

C5.14

JOB NO. 2200393.00

LAND USE RESUBMITTAL: 1/11/2023

220039300\DRAWINGS\CIVIL\393-C5.14.DWG RLF 01/04/23 12:03 1:1



220039300\DRAWINGS\CIVIL\393-C5.14.DWG RLF 01/04/23 12:03 1:1

Delta	Issued As	Issue Date

SHEET INDEX

L0.01	LANDSCAPE GENERAL INFORMATION
L0.02	CWS SCHEDULE AND NOTES
L1.10	PLANTING PLAN
L1.11	PLANTING PLAN
L2.10	IRRIGATION PLAN
L2.11	IRRIGATION PLAN
L5.10	PLANTING DETAILS
L5.11	STORMWATER AND IRRIGATION DETAILS
L5.12	DRIP IRRIGATION DETAILS

TABLE OF ABBREVIATIONS

B&B	BALL AND BURLAP	POC	POINT OF CONNECTION
CAL	CALIPER	PVC	POLY VINYL CHLORIDE
GAL	GALLON	SCH	SCHEDULE

SITE INFORMATION

JURISDICTION	CITY OF SHERWOOD
STORMWATER	CWS
ZONE	LIGHT INDUSTRIAL

ZONING COMPLIANCE

TAX LOT LANDSCAPE AREA	1,007,200 SF
SUBJECT SITE AREA	175,001 SF
SUBJECT SITE LANDSCAPE AREA	91,125 SF
PARKING STALL COUNT	113 STALLS
PARKING LOT LANDSCAPE AREA REQUIRED (45 SF/STALL)	5,085 SF (113 STALLS)
PARKING LOT LANDSCAPING PROVIDED	55,363 SF
PARKING LOT SHRUBS PROVIDED (2 SHRUBS/STALL)	242 (121 STALLS)
PERIMETER LANDSCAPE BUFFER WIDTH (10' MIN)	10'
SUBJECT SITE OVERALL TREE CANOPY COVERAGE	68,688 SF (39%)

PARKING AREA TREE REQUIREMENTS

TREE SPECIES	QUANTITY	SIZE CLASSIFICATION	MATURE CANOPY AREA (SF)	TOTAL MATURE CANOPY COVERAGE (SF)
CLADRASTIS KENTUKEA	12	LARGE	1,964	23,568
THUJA PLICATA 'HOGAN'	2	SMALL	177	354
TILIA TOMENTOSA 'STERLING'	8	MEDIUM	1,256	10,048
ZELKOVA SERRATA 'GREEN VASE'	10	LARGE	1,964	19,640
TREE TOTAL		32 TREES		
TOTAL CANOPY COVERAGE (SF)				51,610

TOTAL STALLS		115 STALLS
SMALL TREES EQUIVALENT (1 PER 2 STALLS)	2 TREES	4 STALLS
MEDIUM TREES EQUIVALENT (1 PER 3 STALLS)	8 TREES	24 STALLS
LARGE TREES EQUIVALENT (1 PER 4 STALLS)	22 TREES	88 STALLS
TOTAL STALL EQUIVALENT PROVIDED		116 STALLS
TOTAL TREES	32 TREES	
EVERGREEN TREES	2 TREES	
EVERGREEN TREES (5% MIN)	6%	























TREE CODE NOTES

- CALCULATIONS ARE ONLY FOR PROPOSED ON-SITE TREES. CALCULATIONS DO NOT INCLUDE EXISTING TREES ON-SITE, TREES IN R.O.W., TREES IN WETLAND OR VEGETATED CORRIDOR (VC) AREAS, OR TREES IN WATER QUALITY/STORMWATER AREAS. FOR TREES IN STORMWATER AND VC AREAS, REFER TO L0.02.

PLANTING SCHEDULE NOTES

- PLANT SCHEDULE ON THIS SHEET EXCLUDES STORMWATER, WETLAND, AND VEGETATED CORRIDOR AREAS AND ROW PLANTING AREAS.
- FOR STORMWATER PLANTING NOTES AND SCHEDULE, REFER TO SHEET L0.02.
- FOR VEGETATED CORRIDOR NOTES AND SCHEDULE, REFER TO SHEET L0.02.

PLANT SCHEDULE

TREES	BOTANICAL / COMMON NAME	SIZE		QTY
	ACER RUBRUM 'FRANKSRED' RED SUNSET MAPLE MATURE SIZE 40' H X 40' W	2" CAL., B&B		6
	CLADRASTIS KENTUKEA AMERICAN YELLOWWOOD MATURE SIZE 40' H X 40' W	2" CAL., B&B		12
	THUJA PLICATA 'HOGAN' HOGAN CEDAR MATURE SIZE 20' H X 15' W	6" HT. MIN. B&B		2
	TILIA TOMENTOSA 'STERLING' STERLING SILVER LINDEN MATURE SIZE 35' H X 30' W	2" CAL., B&B		14
	ZELKOVA SIERRATA 'GREEN VASE' GREEN VASE SAWLEAF ZELKOVA MATURE SIZE 50' H X 50' W	2" CAL., B&B		10
SHRUBS	BOTANICAL / COMMON NAME	SIZE	SPACING	QTY
	BERBERIS THUNBERGII 'CRIMSON PYGMY' CRIMSON PYGMY JAPANESE BARBERRY MATURE SIZE 2' H X 2' W	2 GAL.	24" o.c.	201
	CALAMAGROSTIS X ACUTIFLORA 'OVERDAM' OVERDAM FEATHER REED GRASS MATURE SIZE 2' H X 2' W	1 GAL.	24" o.c.	239
	CISTUS X HYBRIDUS WHITE ROCKROSE MATURE SIZE 4' H X 4' W	2 GAL.	36" o.c.	81
	FOTHERGILLA GARDENII DWARF FOTHERGILLA MATURE SIZE 4' H X 4' W	2 GAL.	36" o.c.	45
	HYDRANGEA QUERCIFOLIA 'PEE WEE' PEE WEE OAKLEAF HYDRANGEA MATURE SIZE 4' H X 3' W	2 GAL.	36" o.c.	21
	PENNISETUM ALOPECUROIDES 'HAMELN' HAMELN FOUNTAIN GRASS MATURE SIZE 2' H X 2.5' W	5 GAL.	36" o.c.	83
	PIERIS JAPONICA 'PRELUDE' PRELUDE JAPANESE PIERIS MATURE SIZE 3' H X 3' W	2 GAL.	36" o.c.	104
	PRUNUS LAUROCERASUS 'OTTO LUYKEN' OTTO LUYKEN LAUREL MATURE SIZE 4' H X 4' W	2 GAL.	42" o.c.	48
	SPIRAEA JAPONICA 'GOLDMOUND' GOLDMOUND SPIREA 3' H X 3' W	2 GAL.	36" o.c.	144
	VIBURNUM DAVIDII DAVID VIBURNUM MATURE SIZE 3' H X 4' W	2 GAL.	36" o.c.	200
	VIBURNUM TINUS 'SPRING BOUQUET' SPRING BOUQUET LAURUSTINUS MATURE SIZE 4' H X 5' W	3 GAL.	48" o.c.	29
GROUND COVERS	BOTANICAL / COMMON NAME	SIZE	SPACING	QTY
	ARCTOSTAPHYLOS UVA-URSI KINKIKINNICK	1 GAL.	24" o.c.	1,257
	MAHONIA REPENS CREEPING MAHONIA	1 GAL.	24" o.c.	691
	SEED MIX NATIVE UPLAND MIX BY SUNMARK SEEDS	1 LB / 1000 SF		19,321 SF
	SEED MIX TYPE 1 KNEE HIGH LOW PROFILE POLLINATOR MIX	1 LB / 1000 SF		4,392 SF
	STORMWATER PLANTING ZONE A	1 GAL.		14,480 SF
	STORMWATER PLANTING ZONE B	1 GAL.		13,139 SF

LANDSCAPE NOTES

GENERAL

- CONTRACTOR SHALL CONFIRM ALL EXISTING CONDITIONS PRIOR TO COMMENCING WORK.
- CALL BEFORE YOU DIG. CONTRACTOR SHALL VERIFY INVERT ELEVATIONS OF ALL UNDERGROUND UTILITIES AND NOTIFY LANDSCAPE ARCHITECT IF THERE ARE ANY DISCREPANCIES WITH PLANTING ROOT ZONES. TO REQUEST LOCATES FOR PROPOSED EXCAVATION CALL 1-800-332-2344 (OR 811) IN OREGON.
- NOTIFY THE OWNER OR OWNER'S REPRESENTATIVE OF ANY DISCREPANCIES OR CONFLICTS WITH EXISTING CONDITIONS PRIOR TO COMMENCEMENT OF ANY WORK.
- LOCATION OF EXISTING TREES SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR PRIOR TO COMMENCEMENT OF WORK.
- DAMAGE TO EXISTING CONCRETE CURB, ASPHALT PAVING, OR OTHER STRUCTURE SHALL BE REPAIRED OR REPLACED TO PRE CONSTRUCTION CONDITIONS.
- CONTRACTOR SHALL COORDINATE WITH THE OWNER ANY DISRUPTION TO VEHICULAR CIRCULATION PRIOR TO COMMENCEMENT OF ANY WORK.


PLANTING


- ALL EXISTING TREES, PLANTS, AND ROOTS SHALL BE PROTECTED FROM DAMAGE FROM ANY CONSTRUCTION PREPARATION, REMOVAL OR INSTALLATION ACTIVITIES WITHIN AND ADJACENT TO PROJECT LIMITS.
- SHRUBS ADJACENT TO PARKING AREAS SHALL BE PLANTED 2 FT MINIMUM AWAY FROM THE BACK OF CURB. SHRUBS AND GROUNDCOVER ALONG OTHER PAVEMENT EDGES SHALL BE PLANTED A MINIMUM OF ONE HALF THEIR ON CENTER SPACING AWAY FROM PAVEMENT EDGE.
- ALL PLANT MATERIAL SHALL BE HEALTHY NURSERY STOCK, WELL BRANCHED AND ROOTED, FULL FOLIAGE, FREE FROM INSECTS, DISEASES, WEEDS, WEED ROT, INJURIES AND DEFECTS WITH NO LESS THAN MINIMUMS SPECIFIED IN AMERICAN STANDARDS FOR NURSERY STOCK, ANSI Z60.1-2004.
- TREES IN THE RIGHT OF WAY SHALL BE TALL ENOUGH TO BE LIMBED UP TO AT LEAST 8 FT ABOVE DRIVE SURFACE GRADE WHILE MAINTAINING ENOUGH BRANCHES TO SUPPORT HEALTHY GROWTH.
- DO NOT PLANT TREES ABOVE WATERLINES, UTILITIES, OR OTHER UNDERGROUND PIPING.
- TREES PLANTED WITHIN 8' OF A UTILITY LINE OR STRUCTURE REQUIRES ROOT BARRIER, SEE DETAIL 3/L5.10
- IF DISTURBANCE IS NECESSARY AROUND EXISTING TREES, CONTRACTOR SHALL PROTECT THE CROWN AND ALL WORK WITHIN THE TREE DRIPZONE SHALL BE LIMITED TO THE USE OF HAND TOOLS AND MANUAL EQUIPMENT ONLY.
- REPLACE, REPAIR AND RESTORE DISTURBED LANDSCAPE AREAS DUE TO GRADING, TRENCHING OR OTHER REASONS TO PRE-CONSTRUCTION CONDITION AND PROVIDE MATERIAL APPROVED BY THE OWNER AND OWNER'S REPRESENTATIVE.
- EXISTING AREAS PROPOSED FOR NEW PLANT MATERIAL SHALL BE CLEARED AND LEGALLY DISPOSED UNLESS SO NOTED.
- A SOILS ANALYSIS, BY AN INDEPENDENT SOILS TESTING LABORATORY RECOGNIZED BY THE STATE DEPARTMENT OF AGRICULTURE, SHALL BE USED TO RECOMMEND AN APPROPRIATE PLANTING SOIL AND/OR SPECIFIED SOIL AMENDMENTS.
- TOPSOIL SHALL BE AMENDED AS RECOMMENDED BY AN INDEPENDENT SOILS TESTING LABORATORY AND AS OUTLINED IN THE SPECIFICATION.
- ALL LANDSCAPED AREAS SHALL BE COVERED BY A LAYER OF ORGANIC MULCH TO A MINIMUM DEPTH OF 2-INCHES.

DESIGN BUILD IRRIGATION

- ALL NEW LANDSCAPE AREAS TO BE IRRIGATED WITH A HIGH EFFICIENCY PERMANENT FULLY AUTOMATIC DRIP IRRIGATION SYSTEM.
- CONTRACTOR SHALL COORDINATE FINAL CONTROLLER LOCATIONS WITH OWNER/OWNERS REPRESENTATIVE.
- VALVES SHALL BE WIRED AND INSTALLED PER MANUFACTURER'S RECOMMENDED INSTALLATION PROCEDURES AND CONNECTED TO THE IRRIGATION CONTROLLER. DO NOT PLACE VALVES IN HIGH VISIBILITY AREAS.
- PROVIDE SLEEVEING AT ALL AREAS WHERE PIPE TRAVELS UNDER CONCRETE OR HARD SURFACING.
- IRRIGATION SYSTEM AS DESIGNED AND INSTALLED SHALL PERFORM WITHIN THE TOLERANCES AND SPECIFICATIONS OF THE SPECIFIED MANUFACTURERS.
- ALL IRRIGATION PIPE MATERIAL AND INSTALLATION SHALL CONFORM TO APPLICABLE CODE FOR PIPING AND COMPONENT REQUIREMENTS.
- SYSTEM SHALL SUPPLY MANUFACTURER'S SPECIFIED MINIMUM OPERATING PRESSURE TO FARTHEST EMITTER FROM WATER METER.
- ALL LATERAL LINES TO BE NO LESS THAN 3/4"
- SYSTEM SHALL INCLUDE SOIL MOISTURE SENSORS. SHOW TYPE AND LOCATION ON SHOP DRAWINGS.
- REF. CIVIL DETAILS FOR POINT OF CONNECTION AND BACKFLOW PREVENTION INFORMATION.
- PROVIDE SHOP DRAWINGS FOR REVIEW PRIOR TO PURCHASE OR INSTALLATION OF SYSTEM. DRAWINGS TO INDICATE GALLONS PER MINUTE PER ZONE, LATERAL LINES, AND BE AT A MINIMUM SCALE OF 1"=20'.
- REFERENCE L5.11 AND L5.12 FOR DESIGN BUILD IRRIGATION DETAILS.

STORMWATER PLANT SCHEDULE

HERBACEOUS	ZONE A (14,480 SF)							
	SCIENTIFIC NAME (COMMON NAME)	QTY.	PLANT CATEGORY	LIGHT REQUIREMENTS	MIN. SIZE AT INSTALLATION	MIN. HEIGHT AT INSTALLATION (1" DIA.)	SPACING	SPACING FORMAT
	CAREX DENSE (DENSE SEDGE)	13032	HERB.	SUN	PLUGS	12"	24"	MASS
	CAREX STIPATA (SAWBEAK SEDGE)	13032	HERB.	SUN	PLUGS	12"	20"	MASS
	SCIRPUS MICROCARPUS (SMALL-FRUITED BULRUSH)	12163	HERB.	SUN	PLUGS	12"	24"	MASS
	JUNCUS PATENS (SPREADING RUSH)	12163	HERB.	SUN	PLUGS	12"	36"	MASS
	JUNCUS TENUIS (SLENDER RUSH)	12163	HERB.	SUN	PLUGS	12"	36"	MASS
	JUNCUS ENSIFOLIUS (DAGGER-LEAF RUSH)	12163	HERB.	SUN	PLUGS	6"	10"	MASS
	CAMASSIA QUAMASH (COMMON CAMAS)	12163	HERB.	SUN	PLUGS	12"	24"	MASS
TOTAL		86,879						

SHRUBS	ZONE B (13,319 SF)							
	SCIENTIFIC NAME (COMMON NAME)	QTY.	PLANT CATEGORY	LIGHT REQUIREMENTS	MIN. SIZE AT INSTALLATION	MIN. HEIGHT AT INSTALLATION (1" DIA.)	SPACING	SPACING FORMAT
	LONICERA INVOLUCRATA (BLACK TWINBERRY)	79	SHRUB	PART	1 GAL.	1'-0"	2'-0" O.C.	MASS
	MAHONIA AQUAFOLIUM (OREGON GRAPE)	79	SHRUB	PART	1 GAL.	1'-0"	2'-0" O.C.	MASS
	PHYSOCARPUS CAPITATUS (PACIFIC NINEBARK)	72	SHRUB	PART	1 GAL.	2'-0"	4'-0" O.C.	CLUSTER
	RIBES SANGUINEUM (RED FLOWERING CURRANT)	66	SHRUB	PART	1 GAL.	2'-0"	4'-0" O.C.	CLUSTER
	ROSA PISOCARPA (CLUSTERED WILD ROSE)	66	SHRUB	PART	1 GAL.	2'-0"	4'-0" O.C.	CLUSTER
	SPIRAEA DOUGLASII (WESTERN SPIREA)	66	SHRUB	PART	1 GAL.	2'-0"	4'-0" O.C.	CLUSTER
	SYMPHORICARPOS ALBUS (SNOWBERRY)	66	SHRUB	PART	1 GAL.	1'-0"	2'-0" O.C.	MASS
TOTAL		494						

TREES	CRATAEGUS DOUGLASII (BLACK HAWTHORN)	26	TREE	SUN	1 GAL.	3'-0"	6'-0" O.C.	CLUSTER
	MALUS FUSCA (OREGON CRAB APPLE)	26	TREE	PART	1 GAL.	3'-0"	6'-0" O.C.	CLUSTER
	QUERCUS GARRYANA (OREGON WHITE OAK)	39	TREE	PART	1 GAL.	3'-0"	10'-0" O.C.	CLUSTER
	THUJA PLICATA 'HOGAN' (HOGAN WESTERN RED CEDAR)	39	TREE	PART	1 GAL.	3'-0"	10'-0" O.C.	SINGLE
	TOTAL		130					

- NOTES:**
- PLANT AND SEED TO ACHIEVE 100% AREAL COVERAGE. OVERSEED ZONE B WITH CWS SEED MIX PT 498 NATIVE RIPARIAN MIX
 - SPACING FORMAT:
 - SINGLE=DISTRIBUTE THROUGHOUT PLANTING AREA
 - CLUSTER=GROUPS OF 3, 5, 7, OR 9, IN SAME AREA
 - MASS=PLANT DENSELY TO FORM A SINGLE STAND OF THAT SPECIES IN A GIVEN AREA
 - AS SHOWN=PLACE AS INDICATED ON PLANTING PLAN

CLEAN WATER SERVICES FACILITY NOTES

SOIL NOTES

- EROSION CONTROL: GRADING, SOIL PREPARATION, AND SEEDING SHALL BE PERFORMED DURING OPTIMAL WEATHER CONDITIONS AND AT LOW FLOW LEVELS TO MINIMIZE SEDIMENT IMPACTS. WHERE SEEDING IS USED FOR EROSION CONTROL, REGREEN, STERILE WHEAT, OR BIODEGRADABLE FABRICS SHALL BE USED TO STABILIZE SLOPES UNTIL PERMANENT VEGETATION IS ESTABLISHED.
- TOPSOIL AT STORMWATER FACILITIES MAY BE SOURCED FROM STOCKPILED SOIL ON SITE. TOPSOIL SHALL CONFORM TO THE CLEAN WATER SERVICES DESIGN AND CONSTRUCTION STANDARDS AND, IF IMPORTED, BE FROM AN APPROVED SOURCE. GROWING MEDIUM FOR STORMWATER FACILITIES SHALL BE A SANDY LOAM SOIL ACCORDING TO USDA SOIL TEXTURE TRIANGLE. TOPSOIL TO BE LOOSE, FRIABLE, WELL BLENDED AND FREE OF DEBRIS, WOOD, WEEDS OR OTHER FOREIGN MATTER.
- TOPSOIL TO BE TESTED BY AN INDEPENDENT LABORATORY, RECOGNIZED BY THE STATE DEPARTMENT OF AGRICULTURE, WITH THE CAPABILITY TO CONDUCT THE TESTING INDICATED. FOLLOW TEXTURAL AND pH RECOMMENDATIONS FROM SOIL TEST.
- COMPOST SHALL BE WELL-COMPOSTED, STABLE, AND WEED FREE ORGANIC MATTER. MOISTURE CONTENT TO BE 35-55% BY WEIGHT, 100% PASSING THROUGH ½ SIEVE, HAVE A SOLUBLE SALT CONTENT OF 5-10 dS/M NOT EXCEEDING .5% INERT CONTAMINANTS AND FREE OF SUBSTANCES TOXIC TO PLANTS.
- AMENDED TOPSOIL AT STORMWATER FACILITIES SHALL HAVE A pH OF 5 TO 8, PASS THROUGH A ONE INCH SCREEN AND CONSIST OF 35% ORGANIC MATTER. PLACE 12" DEPTH MINIMUM OF COMPOST-AMENDED TOPSOIL.
- EXISTING SOIL MAY REMAIN WITHIN VEGETATED CORRIDOR AS GROWING MEDIUM IF IT MEETS SPECIFICATIONS OF THESE NOTES. PIT PLANT ALL TREES AND SHRUBS WITHIN VEGETATED CORRIDOR. REPLACE, REPAIR AND RESTORE DISTURBED LANDSCAPE AREAS DUE TO GRADING, TRENCHING OR OTHER REASONS TO PRE CONSTRUCTION CONDITION AND PROVIDE MATERIAL APPROVED BY THE OWNER OR OWNER'S REPRESENTATIVE.

PLANTING NOTES

- GENERAL**
- QUANTITIES FOR REFERENCE ONLY.
 - UPLAND PLANTING AREAS SHALL BE MULCHED WITH 3" DEPTH MINIMUM WELL-COMPOSTED BARK OR LEAF MATTER.
 - DO NOT APPLY FERTILIZER TO STORMWATER FACILITIES OR VEGETATED CORRIDOR PLANTING AREAS.
 - DO NOT PLANT IN WEATHER ABOVE 90 DEG. OR BELOW 32 DEG.
 - PROTECT STORED ON-SITE PLANT MATERIAL FROM EXTREME HEAT, CHILL OR WIND.
 - ALL PLANT MATERIAL SHALL BE HEALTHY NURSERY STOCK, WELL BRANCHED AND ROOTED, FULL FOLIAGE, FREE FROM INSECTS, DISEASES, WEEDS, WEED ROT, INJURIES AND DEFECTS WITH NO LESS THAN MINIMUMS SPECIFIED IN AMERICAN STANDARDS FOR NURSERY STOCK, ANSI Z60.1-2004.
 - ALL PLANT MATERIAL TO HAVE A MINIMUM HEIGHT OF 6" ABOVE ANY STANDING WATER AT THE TIME OF INSTALLATION.
 - PROVIDE LANDSCAPE ARCHITECT WITH PLANT MATERIAL ORDER FORM WITHIN 30 DAYS OF CONTRACT AWARD.
 - ALL PLANT MATERIAL TO HAVE IDENTIFICATION TAGS TO REMAIN ON PLANT AFTER PLANTING.
 - REMOVE POTS, TWINE AND BURLAP FROM ALL PLANT MATERIAL PRIOR TO PLANTING.
 - SCARIFY ALL ROOTBALLS AND LOOSEN ROOTS PRIOR TO PLANTING.
 - SEE L5.10 FOR PLANTING DETAILS.
 - AT CLOSE OF PROJECT REMOVE ALL EXTRA MATERIALS, SUPPLIES, AND EQUIPMENT FROM SITE.
- PLANTING**
- ALL INVASIVE, NON-NATIVE OR NOXIOUS PLANT MATERIAL IS TO BE REMOVED. METHODS FOR REMOVAL AND CONTROL OF INVASIVE/NON-NATIVE AND/OR NOXIOUS PLANTS ARE TO FOLLOW STRATEGIES AS OUTLINED WITHIN THE CWS IVAM GUIDANCE MANUAL. THE SUBJECT SITE IS TO EMPLOY MANUAL/MECHANICAL MANAGEMENT STRATEGIES AND PESTICIDE MANAGEMENT STRATEGIES THROUGHOUT MAINTENANCE PERIOD OR UNTIL HEALTHY STAND OF DESIRABLE VEGETATION IS ESTABLISHED.
 - PRESERVE SITE'S EXISTING NATIVE VEGETATION TO THE MAXIMUM EXTENT PRACTICABLE. EVERY EFFORT SHALL BE MADE TO PROTECT A SITE'S EXISTING NATIVE VEGETATION. NATIVE VEGETATION ALONG SENSITIVE AREAS AND VEGETATED CORRIDORS SHALL BE RETAINED TO THE MAXIMUM EXTENT PRACTICABLE.
 - REPLANTING/ENHANCEMENT AS FOLLOWS:
 - REFER TO PLANT SCHEDULE AND PLAN FOR PLANT SPECIES, LOCATION, DISTRIBUTION, QUANTITIES, SIZE, CONDITION AND REQUIREMENTS.
 - A NATIVE SEED MIX HAS BEEN SPECIFIED FOR THE BUFFER AREA ONLY. ALL PLANTS TO BE PIT PLANTED WITH ADDITIONAL ORGANIC MATTER IF REQUIRED BUT NO TRADITIONAL FERTILIZER IS NECESSARY. PLANT PLACEMENT SHALL BE CONSISTENT WITH THE FORM OF THE NATURALLY OCCURRING PLANT COMMUNITY. SHRUBS SHALL BE PLACED IN SINGLES OR CLUSTERS OF THE SAME SPECIES TO PROVIDE A NATURAL PLANTING SCHEME.
 - PLANT INSTALLATION REQUIREMENTS. THE CONTRACTOR IS RESPONSIBLE FOR INSTALLATION OF SITE PLANTING AS SPECIFIED ALL TREES AND SHRUBS PLANTED IN THE UPLAND AREA ARE TO BE MULCHED A MINIMUM OF THREE INCHES IN DEPTH AND 18 INCHES IN DIAMETER. APPROPRIATE MULCHES INCLUDE THOSE MADE FROM COMPOSTED LEAVES OR BARK THAT HAVE NOT BEEN CHEMICALLY TREATED. TEMPORARY IRRIGATION WILL BE PROVIDED AND USED DURING THE TWO YEAR MAINTENANCE PERIOD. MONITORING AND MAINTENANCE. CONTRACTOR IS RESPONSIBLE FOR MONITORING AND MAINTAINING THE SITE. ALL NEW PLANT MATERIAL IS TO BE TAGGED. THE REMOVAL OF NON-NATIVE, INVASIVE WEEDS IS NECESSARY THROUGHOUT THE TWO YEAR MAINTENANCE PERIOD, OR UNTIL A HEALTHY STAND OF DESIRABLE VEGETATION IS ESTABLISHED. THE SITE IS TO BE MONITORED A MIN. OF 4 TIMES PER YEAR, OR 3 TIMES PER GROWING SEASON. IF AT ANY TIME THE LANDSCAPING FALLS BELOW THE 80% SURVIVAL LEVEL, THE CONTRACTOR SHALL REINSTALL ALL DEFICIENT PLANTING AT THE NEXT APPROPRIATE OPPORTUNITY AND THE TWO YEAR MAINTENANCE PERIOD SHALL BEGIN AGAIN FROM THE DATE OF THE REPLANTING.
 - CONTRACTOR IS REQUIRED TO PROVIDE AND INSTALL A TEMPORARY IRRIGATION SYSTEM TO MAINTAIN VEGETATIVE CORRIDOR PLANT ESTABLISHMENT DURING THE MONITORING AND MAINTENANCE PERIOD. THE IRRIGATION SYSTEM WILL BE FED FROM A CITY-OWNED METER AND SHALL BE DESIGNED TO NOT EXCEED SITE AVAILABLE GPM AND PSI. REFER TO IRRIGATION INDUSTRY BEST PRACTICES AND STANDARDS FOR ACCEPTABLE DESIGN/BUILD PRACTICES. CONTRACTOR TO PROVIDE IRRIGATION AS-BUILT RECORD DRAWING UPON COMPLETION AND ACCEPTANCE OF IRRIGATION SYSTEM.
 - PLANT TIMING. CONTAINERIZED STOCK SHALL BE INSTALLED ONLY FROM FEBRUARY 1 THROUGH MAY 1 AND OCTOBER 1 THROUGH NOVEMBER 15. BARE ROOT STOCK SHALL BE INSTALLED ONLY FROM DECEMBER 15 THROUGH APRIL 15. PLANTINGS OUTSIDE THESE TIMES MAY REQUIRE ADDITIONAL MEASURES TO ENSURE SURVIVAL WHICH SHALL BE SPECIFIED ON THE PLANS.

MAINTENANCE NOTES

- THE PERMITEE IS RESPONSIBLE FOR PROVIDING ROUTINE MAINTENANCE TO STORMWATER FACILITIES AND VEGETATED CORRIDOR PLANTING AREAS TO ASSESS PLANT ESTABLISHMENT AND IRRIGATION FUNCTIONALITY. ROUTINE MAINTENANCE AT A MINIMUM INCLUDES THREE VISITS PER GROWING SEASON AND ONE VISIT PRIOR TO GROWING SEASON. MAINTENANCE SHALL INCLUDE THE REMOVAL OF NON-NATIVE, INVASIVE WEEDS THROUGHOUT THE MAINTENANCE PERIOD UNTIL A HEALTHY STAND OF VEGETATION IS ACHIEVED.
- MAINTENANCE PERIOD BEGINS AFTER APPROVAL / SIGN OFF OF FINAL INSPECTION OF VEGETATION.
- MAINTENANCE OF VEGETATED CORRIDORS AND STORMWATER FACILITIES TO BE FOR A PERIOD OF TWO YEARS.
- PLANTS FAILING TO MEET ACCEPTANCE CRITERIA SHALL BE REPLACED DURING THE MAINTENANCE PERIOD. PRIOR TO REPLACEMENT, THE CAUSE OF THE LOSS SHALL BE DOCUMENTED AND CORRECTED. THE CITY OF SHERWOOD SHALL INSPECT THE CONDITION OF THE WATER QUALITY/QUANTITY FACILITY AND THE VEGETATED CORRIDOR LANDSCAPING PERIODICALLY THROUGHOUT THE REQUIRED MAINTENANCE PERIOD. THE CITY OF SHERWOOD OF CITY SHALL PROVIDE AN INTERIM INSPECTION REPORT TO THE OWNER WITH A SPECIFIC SUMMARY OF ANY DEFICIENCIES. FAILURE OF THE THE CITY OF SHERWOOD OR CITY TO PROVIDE THE INTERIM REPORT SHALL NOT RELEASE THE OWNER FROM THEIR RESPONSIBILITY TO PROVIDE ESTABLISHED LANDSCAPING AT THE END TO THE REQUIRED LANDSCAPING MAINTENANCE PERIOD.
- IF AT ANY TIME DURING THE WARRANTY PERIOD THE LANDSCAPING FALLS BELOW 80% SURVIVAL OF TREES AND SHRUBS, OR 90% COVERAGE BY HERBACEOUS PLANTS, OR IF THE AMOUNT OF UNDESIRABLE VEGETATION COVER INCLUDING TARGET NON-NATIVE SPECIES EXCEEDS 10%, THE OWNER SHALL REMOVE UNDESIRABLE VEGETATION AND REINSTALL ALL DEFICIENT PLANTING AT THE NEXT APPROPRIATE PLANTING OPPORTUNITY. THE REQUIRED MAINTENANCE PERIOD MAY BE EXTENDED FROM THE DATE OF REPLANTING IF, IN THE OPINION OF THE CITY, AN ADDITIONAL TIME PERIOD IS NEEDED TO ENSURE THE REQUIRED LANDSCAPING BECOMES ESTABLISHED AND CAN SURVIVE LONG TERM. THE EXTENSION OF THE WARRANTY PERIOD MAY BE UP TO TWO YEARS.
- THE WARRANTY PERIOD SHALL BE COMPLETE WHEN ALL THE REQUIREMENTS OF SECTION 2.08 OF THE CWS MANUAL HAVE BEEN MET. THE ONE YEAR MAINTENANCE ASSURANCE PERIOD HAS EXPIRED ON ALL ELEMENTS OF THE PROJECT AND ANY REPAIRS REQUIRED DURING THE MAINTENANCE PERIOD HAVE BEEN COMPLETED AND ACCEPTED.

WATER QUALITY PROTECTION NOTES

- NO STRUCTURES, DEVELOPMENT, CONSTRUCTION ACTIVITIES, GARDENS, LAWNS, APPLICATION OF CHEMICALS, UNCONTAINED AREAS OF HAZARDOUS MATERIALS AS DEFINED BY DEQ, PET WASTES, DUMPING OF MATERIALS OF ANY KIND, OR OTHER ACTIVITIES SHALL BE PERMITTED WITHIN THE SENSITIVE AREA OR VEGETATED CORRIDOR WHICH MAY NEGATIVELY IMPACT WATER QUALITY, EXCEPT THOSE ALLOWED IN R&O 07-20, CHAPTER THREE.
- IF APPLICABLE, PRIOR TO ANY SITE CLEARING, GRADING OR CONSTRUCTION, THE VEGETATED CORRIDOR AND WATER QUALITY SENSITIVE AREAS SHALL BE SURVEYED, STAKED AND TEMPORARILY FENCED PER APPROVED PLAN. DURING CONSTRUCTION THE VEGETATED CORRIDOR SHALL REMAIN FENCED AND UNDISTURBED EXCEPT AS ALLOWED BY R&O 07-20 SECTION 3.06.1 AND PER APPROVED PLANS.
- IF THERE IS ANY ACTIVITY WITHIN THE SENSITIVE AREA, THE APPLICANT SHALL GAIN AUTHORIZATION FOR THE PROJECT FROM THE OREGON DEPARTMENT OF STATE LANDS AND THE UNITED STATES ARMY CORPS OF ENGINEERS. THE APPLICATION SHALL PROVIDE THE CITY OF SHERWOOD WITH COPIES OF ALL DSL AND USACE PROJECT AUTHORIZATION PERMITS.
- APPROPRIATE BMP'S FOR EROSION CONTROL, IN ACCORDANCE WITH CWS' EROSION PREVENTION AND SEDIMENT CONTROL PLANNING AND DESIGN MANUAL SHALL BE USED PRIOR TO, DURING, AND FOLLOWING EARTH DISTURBING ACTIVITIES.
- REMOVAL OF NATIVE, WOODY VEGETATION SHALL BE MINIMIZED TO THE GREATEST EXTENT PRACTICABLE.

IRRIGATION NOTES

- PROVIDE IRRIGATION AT A MINIMUM RATE OF ONE INCH PER WEEK FROM JUNE 15 TO OCTOBER 15 OR LONGER IF NEEDED. IRRIGATE PLANT MATERIAL A MINIMUM OF THREE TIMES PER WEEK.
- PLANT MATERIAL TO BE IRRIGATED FOR A MINIMUM PERIOD OF TWO YEARS FROM DATE OF SUBSTANTIAL COMPLETION.
- PROVIDE DESIGN/BUILD TEMPORARY IRRIGATION DESIGN PRIOR TO COMMENCING WORK. AT A MINIMUM, PLAN TO IDENTIFY WATER SOURCE, BACKFLOW PREVENTER, HEAD TYPE AND LAYOUT OF PIPE. IRRIGATION SHALL BE INSTALLED SIMULTANEOUSLY WITH PLANTING TO ENSURE PLANTS RECEIVE ADEQUATE WATER AT TIME OF INSTALLATION.

M.

Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknzie.com

MACKENZIE
DESIGN DRIVEN | CLIENT FOCUSED

Client

ORWA SHERWOOD,
LLC

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project

SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER,
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:



CWS SCHEDULE
AND NOTES

DRAWN BY: RAC, ADS, LJM

CHECKED BY:SPT, NRF

SHEET:



L0.02



- NOTES**
- PLANT SIZE, SPACING, AND QUANTITY, SEE PLANT SCHEDULE L0.01
 - COORDINATE SHRUB LAYOUT WITH EXISTING UTILITIES, REPORT CONFLICTS TO LANDSCAPE ARCHITECT.
 - VEGETATED CORRIDOR PER PACIFIC HABITAT SERVICES NATURAL RESOURCE ASSESSMENT. INSTALLATION BY OTHERS. SHOWN FOR REFERENCE ONLY.

PLANT KEY LEGEND

TREES	BOTANICAL / COMMON NAME
	ACER RUBRUM 'FRANKSRED' RED SUNSET MAPLE
	CLADRASTIS KENTUCKEA AMERICAN YELLOWWOOD
	THUJA PLICATA 'HOGAN' HOGAN CEDAR
	TILIA TOMENTOSA 'STERLING' STERLING SILVER LINDEN
	ZELKOVA SERRATA 'GREEN VASE' GREEN VASE SAWLEAF ZELKOVA
SHRUBS	BOTANICAL / COMMON NAME
	BERBERIS THUNBERGII 'CRIMSON PYGMY' CRIMSON PYGMY JAPANESE BARBERRY
	CALAMAGROSTIS X ACUTIFLORA 'OVERDAM' OVERDAM FEATHER REED GRASS
	CISTUS X HYBRIDUS WHITE ROCKROSE
	FOTHERGILLA GARDENII DWARF FOTHERGILLA
	HYDRANGEA QUERCIFOLIA 'PEE WEE' PEE WEE OAKLEAF HYDRANGEA
	PENNISETUM ALOPECUROIDES 'HAMELN' HAMELN FOUNTAIN GRASS
	PIERIS JAPONICA 'PRELUDE' PRELUDE JAPANESE PIERIS
	PRUNUS LAUROCERASUS 'OTTO LUYKEN' OTTO LUYKEN LAUREL
	SPIRAEA JAPONICA 'GOLDMOUND' GOLDMOUND SPIREA
	VIBURNUM DAVIDII DAVID VIBURNUM
	VIBURNUM TINUS 'SPRING BOUQUET' SPRING BOUQUET LAURUSTINUS
GROUND COVERS	BOTANICAL / COMMON NAME
	ARCTOSTAPHYLOS UVA-URSI KINKINICK
	MAHONIA REPENS CREEPING MAHONIA
	SEED MIX TYPE 1 KNEE HIGH LOW PROFILE POLLINATOR MIX



Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknze.com

MACKENZIE.
DESIGN DRIVEN | CLIENT FOCUSED

Client
ORWA SHERWOOD, LLC

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project
SHERWOOD INDUSTRIAL PARK (PHASE 3)



© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF MACKENZIE AND ARE NOT TO BE USED OR REPRODUCED IN ANY MANNER, WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date


SHEET TITLE:
PLANTING PLAN

DRAWN BY: RAC, ADS, LJM, AB
CHECKED BY: SPT, NRF
SHEET:

L1.10
JOB NO. **2200393.00**



PLANTING PLAN




NOTES

1. PLANT SIZE, SPACING, AND QUANTITY, SEE PLANT SCHEDULE L0.01
2. COORDINATE SHRUB LAYOUT WITH EXISTING UTILITIES, REPORT CONFLICTS TO LANDSCAPE ARCHITECT.
3. VEGETATED CORRIDOR PER PACIFIC HABITAT SERVICES NATURAL RESOURCE ASSESSMENT. INSTALLATION BY OTHERS. SHOWN FOR REFERENCE ONLY.


PLANT KEY LEGEND

TREES	BOTANICAL / COMMON NAME
	THUJA PLICATA 'HOGAN' HOGAN CEDAR
	TILIA TOMENTOSA 'STERLING' STERLING SILVER LINDEN
	ZELKOVA SERRATA 'GREEN VASE' GREEN VASE SAWLEAF ZELKOVA
SHRUBS	BOTANICAL / COMMON NAME
	BERBERIS THUNBERGII 'CRIMSON PYGMY' CRIMSON PYGMY JAPANESE BARBERRY
	CALAMAGROSTIS X ACUTIFLORA 'OVERDAM' OVERDAM FEATHER REED GRASS
	CISTUS X HYBRIDUS WHITE ROCKROSE
	FOTHERGILLA GARDENII DWARF FOTHERGILLA
	PENNISETUM ALOPECUROIDES 'HAMELN' HAMELN FOUNTAIN GRASS
	PIERIS JAPONICA 'PRELUDE' PRELUDE JAPANESE PIERIS
	PRUNUS LAUROCERASUS 'OTTO LUYKEN' OTTO LUYKEN LAUREL
	SPIRAEA JAPONICA 'GOLDMOUND' GOLDMOUND SPIREA
	VIBURNUM DAVIDII DAVID VIBURNUM
	VIBURNUM TINUS 'SPRING BOUQUET' SPRING BOUQUET LAURUSTINUS
GROUND COVERS	BOTANICAL / COMMON NAME
	ARCTOSTAPHYLOS UVA-URSI KINNIKINNICK
	MAHONIA REPENS CREEPING MAHONIA
	SEED MIX TYPE 1 KNEE HIGH LOW PROFILE POLLINATOR MIX
	STORMWATER PLANTING ZONE A
	STORMWATER PLANTING ZONE B



KEY MAP

SCALE: NTS



Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknze.com

MACKENZIE.
DESIGN DRIVEN • CLIENT FOCUSED

Client
**ORWA SHERWOOD,
LLC**

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project
**SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)**

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER,
WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
PLANTING PLAN

DRAWN BY: RAC, ADS, LJM, AB

CHECKED BY: SPT, NRF


SHEET:

L1.11

JOB NO. **2200393.00**

LAND USE RESUBMITTAL: 1/11/2023

220039300 \\GRP\MCK\PROJECTS\PROJECTS\220039300\DRAWINGS\LANDSCAPE\L0.01\L1.11.DWG\L1.11 AB 01/06/23 14:15 1:0.08



IRRIGATION LEGEND

POC

POINT OF CONNECTION, INCLUDE DOUBLE CHECK BACKFLOW PREVENTOR, MASTER VALVE AND FLOW SENSOR - SEE DETAIL ON L5.11

IRRIGATION CONTROLLER

GATE VALVE

QUICK COUPLER AT 200' (INTERVALS MAX)

MAINLINE SLEEVE- DIAMETER AT LEAST TWICE DIAMETER OF PIPE BEING SLEEVED

MAINLINE-SCHEDULE 40 PVC

DRIP IRRIGATION AREA - SEE DETAILS ON L5.12

TEMPORARY IRRIGATION AREA

IRRIGATED STORMWATER AREA

M.

Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknz.com

MACKENZIE.

DESIGN DRIVEN | CLIENT FOCUSED

Client

ORWA SHERWOOD, LLC

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project

SHERWOOD INDUSTRIAL PARK (PHASE 3)

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF MACKENZIE AND ARE NOT TO BE USED OR REPRODUCED IN ANY MANNER, WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:

IRRIGATION PLAN

DRAWN BY: RAC, ADS, LJM, AB

CHECKED BY: SPT, NRF

SHEET:

L2.10

JOB NO. 2200393.00


1 IRRIGATION PLAN

L2.10

20 0 10 20 40 80 (IN FEET)
1 inch = 20 ft.

KEY MAP

SCALE: NTS



IRRIGATION LEGEND

POC POINT OF CONNECTION, INCLUDE DOUBLE CHECK BACKFLOW PREVENTOR, MASTER VALVE AND FLOW SENSOR - SEE DETAIL ON L5.11

IRRIGATION CONTROLLER

GATE VALVE

QUICK COUPLER AT 200' (INTERVALS MAX)

MAINLINE SLEEVE- DIAMETER AT LEAST TWICE DIAMETER OF PIPE BEING SLEEVED

MAINLINE-SCHEDULE 40 PVC

DRIP IRRIGATION AREA - SEE DETAILS ON L5.12

TEMPORARY IRRIGATION AREA

IRRIGATED STORMWATER AREA

M.

Architecture • Interiors
Planning • Engineering

Portland, OR
503.224.9560
Vancouver, WA
360.695.7879
Seattle, WA
206.749.9993
www.mcknzie.com

MACKENZIE.

DESIGN DRIVEN | CLIENT FOCUSED

Client
ORWA SHERWOOD, LLC

8320 NE HIGHWAY 99
VANCOUVER, WA 98665

Project
SHERWOOD INDUSTRIAL PARK (PHASE 3)

© MACKENZIE 2023
ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF MACKENZIE AND ARE NOT TO BE USED OR REPRODUCED IN ANY MANNER, WITHOUT PRIOR WRITTEN PERMISSION

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
IRRIGATION PLAN

DRAWN BY: RAC, ADS, LJM, AB
CHECKED BY: SPT, NRF
SHEET:


L2.11

JOB NO. **2200393.00**

1 IRRIGATION PLAN
L2.11

1 inch = 20 ft.

KEY MAP
SCALE: NTS



REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**PLANTING
DETAILS**











DRAWN BY: RAC/ADS


CHECKED BY: SPT

SHEET:

JOB NO. **2200393.00**

L5.10





NOTES:

TOPSOIL:


1. PROVIDE SOIL AND SIEVE ANALYSIS FOR COMPOST AND AMENDED TOPSOIL FOR REVIEW PRIOR TO INSTALLATION, SEE NOTES ON L2.0A. SUBMIT SAMPLE OF AMENDED TOPSOIL TO LANDSCAPE ARCHITECT FOR ACCEPTANCE PRIOR TO INSTALLATION.
2. REMOVE ALL PLANTS, ROOTS, SEEDS, AS WELL AS ROCK, DEBRIS, AND OTHER FOREIGN MATTER OVER 1" IN DIAMETER FROM TOP 12" OF SOIL. TILL INTERFACE OF SUBGRADE AND TOPSOIL.
3. RIP AND TILL EXISTING SUBGRADE TO 4" DEEP (MIN.) PRIOR TO INSTALLING AMENDED TOPSOIL. INSTALL 12" OF AMENDED TOPSOIL, SEE NOTES L2.0A

PLANTING:

1. SET CROWN OF ROOTBALL FOR TREES AND SHRUBS 1" ABOVE FINISH GRADE AND REMOVE BURLAP AND WIRE BASKETS FROM ROOTBALL.
2. BREAK ROOTBALL APART BEFORE PLACING IN PLANTING HOLE. IF PLANT IS ROOT BOUND, MAKE A VERTICAL CUT THROUGH THE LOWER ¼ OF THE SOIL MASS, PULL OUT AND STRAIGHTEN LARGE, CIRCLING ROOTS.
3. FOR TREES: EXCAVATE PLANTING HOLE TO 3X THE WIDTH OF THE ROOTBALL AT INSTALLATION AND COMPACT AMENDED TOPSOIL AT BOTTOM OF PLANTING PIT PRIOR TO INSTALLATION. INSTALL WELL COMPOSTED BARK OR LEAF MULCH AT A DEPTH OF 3" AND 18" IN DIAMETER AROUND NEWLY INSTALLED PLANT MATERIAL.
4. FOR SHRUBS: EXCAVATE PLANTING HOLE TO 2X THE WIDTH OF THE ROOTBALL AT INSTALLATION AND COMPACT AMENDED TOPSOIL AT BOTTOM OF PLANTING PIT PRIOR TO INSTALLATION. INSTALL WELL COMPOSTED BARK OR LEAF MULCH AT A DEPTH OF 3" AND 18" IN DIAMETER AROUND NEWLY INSTALLED PLANT MATERIAL.
5. FOR PLUGS: AT INSTALLATION, PLUGS TO BE 6" HIGHER THAN ROCK MULCH OR PERMANENT POOL ELEVATION, WHICHEVER IS HIGHER.

1 EXTENDED DRY BASIN SECTION

SCALE: NTS



NOTE:

NOTE:
INSTALL BACKFLOW PREVENTOR PER CODE AND
REQUIREMENTS OF PREVAILING JURISDICTIONS.

2 POINT OF CONNECTION

SCALE: NTS

3 DOUBLE CHECK VALVE BACKFLOW PREVENTOR (BELOW GRADE)

SCALE: NTS

4 QUICK COUPLER VALVE

SCALE: NTS

5 INTERIOR WALL MOUNT CONTROLLER

1" = 1'-0"

FX-IR-FX-CONT-21

project
**SHERWOOD
INDUSTRIAL
PARK
(PHASE 3)**

© MACKENZIE 2023
ALL RIGHTS RESERVED

THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER,
WITHOUT PRIOR WRITTEN PERMISSION

[illegible]

HEET TITLE:
**STORMWATER
AND
IRRIGATION
DETAILS**

RAWN BY: RAC/ADS

CHECKED BY: SPT

HEET:

OB NO. **2200393.00**

LAND USE RESUBMITTAL: 1/11/2023

220039300\DRAWINGS\LANDSCAPE\393-1.5.10-1.5.11.DWG:1.5.11.LJM 09/26/22 21:36 1:0.08

REVISION SCHEDULE		
Delta	Issued As	Issue Date



SHEET TITLE:
**DRIP
IRRIGATION
DETAILS**

DRAWN BY: RAC/ADS
CHECKED BY: SPT
SHEET:

L5.12

JOB NO. **2200393.00**

LAND USE RESUBMITTAL: 1/11/2023
220039300\DRAWINGS\LANDSCAPE\393\L5.10\L5.11.DWG\L5.12 LJM 09/28/22 16:50 1:0.08




5 DRIPLINE AROUND TREE
SCALE: NTS

GENERAL NOTES

- PROVIDE 16'-0" CLEAR MINIMUM TO ALL STRUCTURAL MEMBERS, ELECTRICAL FIXTURES, MECHANICAL UNITS AND FIRE SPRINKLER LINES. SEE BUILDING SECTIONS.
- VERIFY AND CONFIRM ALL DIMENSIONS AND CONDITIONS. NOTIFY ARCHITECT OF ANY DISCREPANCIES PRIOR TO THE START OF CONSTRUCTION.
- SEE STRUCTURAL FOR ADDITIONAL INFORMATION.
- SEE 10 / AS 10 FOR SLAB JOINT DETAILS.
- ALL SLAB JOINTS TO BE CAULKED, INCLUDING POUR-BACK.
- INSTALL DOOR ARMOR PER 7 / AS 11 & 8 / AS 10 AT ALL GRADE ACCESS AND DOCK-HIGH OVERHEAD DOORS.
- COORDINATE SEWER CLEAN-OUT PER CODE, VERIFY ALL LOCATIONS WITH OWNER PRIOR TO CONSTRUCTION.


SYMBOLS LEGEND

KEYNOTE	SYMBOL
GRIDLINE	○
DOCK HIGH OVERHEAD DOOR	▽
DRIVE IN OVERHEAD DOOR	▽
FUTURE OPENING	○
DOOR TAG	○
WINDOW TAG CALLOUT	○
PANEL NUMBER, SEE STRUCTURAL	##
COLUMN LINE	CL
PANEL JOINT	PJ
OUTSIDE FACE	OSF
CLEAN OUT	• CO
DOWNSPOUT LOCATION	• DS
1 HR RATED WALL	■




2 BIKE RACK
5A1.11 1/2" = 1'-0"

3 TRASH ENCLOSURE PLAN
5A1.11 1/4" = 1'-0"



KEYNOTES



1 BLDG 5 - FLOOR PLAN
5A1.11 1/8" = 1'-0"



Architecture - Interiors
Planning - Engineering

Portland, OR
503.234.3560
Vancouver, WA
360.682.7879
Seattle, WA
206.742.2893
www.mackenzie.com

MACKENZIE
ARCHITECTS - ENGINEERS

Client:
ORWA
Sherwood LLC

8320 NE HWY 99
VANCOUVER, WA
98665

Project:
SHERWOOD
INDUSTRIAL PARK
(PHASE 3)
15028 SW CENTURY DR
SHERWOOD, OR 97140

© MACKENZIE
2022 ALL RIGHTS RESERVED
THESE DRAWINGS ARE THE PROPERTY OF
MACKENZIE AND ARE NOT TO BE USED
OR REPRODUCED IN ANY MANNER

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
BLDG 5 -
FLOOR PLAN

DRAWN BY: TJK

CHECKED BY: Checker

SHEET

5A1.11

JOB NO. **2200393.00**

DESIGN REVIEW 09/30/2022

Autodesk Docs/ITBSP - Phase 3/353/150P Phase 3-V22-8.rvt 9/30/2022 12:12:48 PM As Indicated

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**BLDG 5 -
ELEVATIONS**

DRAWN BY: TJK

CHECKED BY: DEP

SHEET




5A2.11

JOB NO. **2200393.00**

GENERAL NOTES

- A. VERIFY AND CONFIRM ALL DIMENSIONS AND CONDITIONS.
NOTIFY ARCHITECT OF ANY DISCREPANCIES PRIOR TO
THE COMMENCEMENT OF CONSTRUCTION.

SYMBOLS LEGEND

- KEYNOTE  0
GRIDLINE  0
WINDOW TYPE, SEE A5.1 


MATERIAL SCHEDULE

- EF-1: PAINTED SHEET METAL, BLACK
EF-2: ANODIZED ALUMINUM/SHEET METAL, CHARCOAL
EF-3: GLAZING, CLEAR
EF-4: BRICK VENEER
EF-5: SHIPLAP WOOD SCREEN
EF-6: CLAPBOARD SLIDING, TOUGHE AND GROVE
SIDING
EF-7: PRECAST BOARD-FORM CONCRETE
EF-8: EXPOSED MASONRY, BLEND
EF-9: METAL PANEL SYSTEM, BRONZE
RF-01: STANDING SEAM METAL ROOF, GRAY
RF-02: SYNTHETIC SLATE ROOF, GRAY

KEYNOTES


GLAZING CALCULATIONS

NORTH ELEVATION	
TOTAL AREA:	1,410 SF
GLAZING AREA:	645 SF
PERCENTAGE:	45.7%
EAST ELEVATION	
TOTAL AREA:	3,470 SF
GLAZING AREA:	1,285 SF
PERCENTAGE:	37%
SOUTH ELEVATION	
TOTAL AREA:	1,380 SF
GLAZING AREA:	583 SF
PERCENTAGE:	42.3%
WEST ELEVATION	
TOTAL AREA:	3,475 SF
GLAZING AREA:	695 SF
PERCENTAGE:	20%




1 BLDG 5 - EAST ELEVATION

5A2.11 1/8" = 1'-0"




3 BLDG 5 - SOUTH ELEVATION

5A2.11 1/8" = 1'-0"




2 BLDG 5 - NORTH ELEVATION

5A2.11 1/8" = 1'-0"



4 BLDG 5 - WEST ELEVATION

5A2.11 1/8" = 1'-0"




GENERAL NOTES

- PROVIDE 16'-0" CLEAR MINIMUM TO ALL STRUCTURAL MEMBERS, ELECTRICAL FIXTURES, MECHANICAL UNITS AND FIRE SPRINKLER LINES. SEE BUILDING SECTIONS.
- VERIFY AND CONFIRM ALL DIMENSIONS AND CONDITIONS. NOTIFY ARCHITECT OF ANY DISCREPANCIES PRIOR TO THE START OF CONSTRUCTION.
- SEE STRUCTURAL FOR ADDITIONAL INFORMATION.
- SEE 10 / AS 10 FOR SLAB JOINT DETAILS.
- ALL SLAB JOINTS TO BE CAULKED, INCLUDING POUR-BACK.
- INSTALL DOOR ARMOR PER 7 / AS 11 & 8 / AS 10 AT ALL GRADE ACCESS AND DOCK-HIGH OVERHEAD DOORS.
- COORDINATE SEWER CLEAN-OUT PER CODE. VERIFY ALL LOCATIONS WITH OWNER PRIOR TO CONSTRUCTION.

SYMBOLS LEGEND

KEYNOTE	00.00
GRIDLINE	0
DOCK HIGH OVERHEAD DOOR	▽
DRIVE IN OVERHEAD DOOR	▽
FUTURE OPENING	101A
DOOR TAG	0
WINDOW TAG CALLOUT	#
PANEL NUMBER, SEE STRUCTURAL	#
COLUMN LINE	CL
PANEL JOINT	PJ
OUTSIDE FACE	OSF
CLEAN OUT	CO
DOWNSPOUT LOCATION	DS
1 HR RATED WALL	



1 BLDG 6 - FLOOR PLAN
6A1.11 1/8" = 1'-0"

REVISION SCHEDULE			
Delta	Issued As	Issue Date	

REVISION SCHEDULE		
Delta	Issued As	Issue Date

SHEET TITLE:
**BLDG 6 -
ELEVATIONS**

DRAWN BY: TJK

CHECKED BY: DEP

SHEET

6A2.11

JOB NO. **2200393.00**

GENERAL NOTES

A. VERIFY AND CONFIRM ALL DIMENSIONS AND CONDITIONS.
NOTIFY ARCHITECT OF ANY DISCREPANCIES PRIOR TO
THE COMMENCEMENT OF CONSTRUCTION.

SYMBOLS LEGEND

KEYNOTE 
GRIDLINE 
WINDOW TYPE, SEE A5.1 

MATERIAL SCHEDULE

EF-1: PAINTED SHEET METAL, BLACK 
EF-2: ANODIZED ALUMINUM SHEET METAL, CHARCOAL 
EF-3: GLAZING, CLEAR 
EF-4: BRICK VENEER 
EF-5: SHIPLAP WOOD SCREEN 
EF-6: CLAPBOARD SLIDING, TOUGUE AND GROVE SIDING 
EF-7: PRECAST BOARD-FORM CONCRETE 
EF-8: EXPOSED MASONRY, BLEND 
EF-9: METAL PANEL SYSTEM, BRONZE 
RF-01: STANDING SEAM METAL ROOF, GRAY 
RF-02: SYNTHETIC SLATE ROOF, GRAY 


KEYNOTES

GLAZING CALCULATIONS


NORTH ELEVATION
TOTAL AREA: 4,190 SF
GLAZING AREA: 950 SF
PERCENTAGE: 22.6%
EAST ELEVATION
TOTAL AREA: 1,505 SF
GLAZING AREA: 615 SF
PERCENTAGE: 40.8%
SOUTH ELEVATION
TOTAL AREA: 4,135 SF
GLAZING AREA: 1,455 SF
PERCENTAGE: 35.2%
WEST ELEVATION
TOTAL AREA: 1,362 SF
GLAZING AREA: 650 SF
PERCENTAGE: 46%

DESIGN REVIEW 09/30/2022


Autodesk Docs/ITBSP - Phase 3/353-TSP Phase 3-V22-B.m 9/30/2022 10:40:09 AM As indicated




4 BLDG 6 - SOUTH ELEVATION
6A2.11 1/8" = 1'-0"




3 BLDG 6 - WEST ELEVATION
6A2.11 1/8" = 1'-0"



2 BLDG 6 - EAST ELEVATION
6A2.11 1/8" = 1'-0"



1 BLDG 6 - NORTH ELEVATION
6A2.11 1/8" = 1'-0"





1 BUILDING 5 - EAST VIEW
A6.11 12" = 1'-0"



2 BUILDING 5 - SE VIEW
A6.11 12" = 1'-0"



3 BUILDING 6 - SW VIEW
A6.11 12" = 1'-0"



4 BUILDING 6 - NW VIEW
A6.11 12" = 1'-0"

REVISION SCHEDULE		
Delta	Issued As	Issue Date