

CROSS SECTION

NOTES:

- TREE SPECIES AND CALIPER SIZE ARE TO BE APPROVED BY THE CITY PLANNING DEPARTMENT.
 ADJUST PLANTING LOCATIONS SO THAT TREE CROWN OR ROOT BALL DOES NOT CONFLICT WITH ABOVE OR BELOW GROUND UTILITIES.
- 3. DO NOT UNDERMINE CURB OR SIDEWALK WHEN EXCAVATING.
- 4. ALL TREES WITH TRUNKS CLOSER THAN 4' TO ASPHALT OR CONCRETE SURFACE SHALL HAVE A MINIMUM OF AN 18" ROOT BARRIER INSTALLED AT 10' IN LENGTH AND CENTERED ON TREE.

 5. PROVIDE A LOOP IN CHAIN—LOCK LARGE ENOUGH TO ALLOW FOR TRUNK GROWTH.

 6. TREE STAKES ARE TO BE REMOVED FOLLOWING THE REQUIRED ESTABLISHMENT PERIOD.

,	STANDARD DRAWING TITLE		DRAWING NUMBER
Sherwood oregon	STREET TREE DETAIL		RD-80
	Any alteration of this drawing may not be associated in any way with the City of Sherwood Standard Drawings.	SCALE	DATE
		N.T.S.	MAR '16