



NOTES:

1. IRRIGATION SLEEVE CROSSING MATERIAL SHALL BE 4"Ø DUCTILE IRON PIPE (DIP). LOCATION OF ALL IRRIGATION SLEEVE CROSSINGS SHALL BE SHOWN ON ALL UTILITY PLAN SHEETS.
2. IRRIGATION SLEEVE CROSSING PIPE SHALL EXTEND TO MIDDLE OF PLANTER STRIPS.
3. IRRIGATION SLEEVE CROSSINGS SHALL BE LOCATED AS NEAR TO LOT LINES AS POSSIBLE, AWAY FROM STREET INTERSECTIONS AND ADA RAMPS.
4. IRRIGATION STREET CROSSINGS SHALL BE LOCATED TO AVOID CONFLICT WITH STREET LIGHTS AND STREET TREES.
5. ENDS OF SLEEVE CROSSING SHALL BE EITHER PLUGGED WITH GROUT OR A RUBBER BOOT ATTACHED TO PREVENT INFILTRATION OF SOIL INTO THE ANNULAR SPACE BETWEEN THE SLEEVE AND IRRIGATION LINE. THE SLEEVE CROSSING SHALL NOT BE FILLED WITH SAND OR SLURRY MIX.
6. IRRIGATION SLEEVE CROSSING LOCATIONS SHALL BE NOTED ON CONSTRUCTION PLANS USING STREET CENTERLINE STATIONING. THE SLEEVE CROSSINGS SHALL BE INSTALLED PERPENDICULAR TO STREET CENTERLINE ALIGNMENT.



STANDARD DRAWING TITLE		DRAWING NUMBER
IRRIGATION SLEEVE STREET CROSSING DETAIL		RD-40
Any alteration of this drawing may not be associated in any way with the City of Sherwood Standard Drawings.	SCALE	DATE
	N.T.S.	MAR '16